



TECSUN[®] Building Products

Tecsun Premium Urethane Wood Flooring Adhesive and Tecsun **Moisture Shield** Concrete Moisture Block & Crack Suppressant are VOC compliant and help contribute to LEED point project credits.

Tecsun Building Products now offers a comprehensive adhesive and concrete sealer system for all your wood flooring and concrete moisture control installation needs. To place an order call Tecsun at (626) 968-7566

Premium Urethane Wood Flooring Adhesive



- Flooring Types**
- Bamboo
 - Parquet
 - Solid Plank Flat-Milled up to 1/2" Thick
 - Exotic Woods
 - Plywood
 - Multi-Ply Engineered Plank
 - Acrylic Impregnated Wood

- Features**
- Easy to Spread
 - Easy to Clean When Wet
 - Non-Slumping
 - Contains No Water
 - Low Odor
 - Nonflammable
 - VOC Compliant
 - Freeze-Thaw Stable
 - High Solids
- Available in 4-gallon containers

TROWELS AND COVERAGE					
Floor Type	Trowel	Coverage	Floor Type	Trowel	Coverage
multi-ply engineered plank 3/8" up to 1/2" and 5/16" to 3/8" solid strip	 3/16" x 3/16" x 5/32" V Notch	50 sq. feet/gal.	3/4" solid shorts, 4' x 4' plywood	 1/4" x 1/4" x 1/4" Square Notch	30 sq. feet/gal.
5/16" solid parquet, 1/4" engineered plank	 1/8" x 1/8" x 1/8" Square Notch	80 sq. feet/gal.	Greater than 1/2" engineered plank, 3/4" parquet and solid plank greater than 3/8" up to 1/2"	 1/4" x 1/4" x 1/8" Square Notch	35 sq. feet/gal.
bamboo up to 5/8" in thickness	 3/16" x 3/16" x 3/16" Square Notch				35 sq. feet/gal.

Moisture Shield Concrete Moisture Blockade & Crack Suppressant

Features

- Significantly Reduces Moisture Vapor Transmission
- One-Part Urethane Moisture Barrier
- Crack Suppressant
- Easy to Apply & Easy to Clean When Wet
- Available in 4-gallon Containers
- Enhanced Moisture Warranty When Used In Conjunction With Tecsun Premium Urethane Wood Flooring Adhesive
- VOC Compliant
- Moisture Cured Urethane Membrane
- Low Odor
- Enhanced Life-Time Moisture Warranty



TROWEL AND COVERAGE		
Floor Type	Trowel	Coverage
	 3/16" x 3/16" x 5/32" V Notch	40-45 sq. feet/gal.

Tecsun Urethane Adhesive Remover

Features

- Removes Wet or Uncured Urethane Adhesive From Wood Flooring Surfaces
- Cleans Tools
- Strong & Effective
- Easy to Use
- Formulated for Professional Installers

Formulated to Remove:

Tecsun Premium Urethane Wood Flooring Adhesive



Tecsun Towels - Green Urethane Adhesive Remover

Features

- Removes Uncured Urethane Adhesive
- Superior Strength & Low Odor
- Water Rinseable Solution
- "Green" Product
- No Harm to Finish
- Easy to Use

Formulated to Remove:

Tecsun Premium Urethane Wood Flooring Adhesive



Tecsun

Premium Urethane Wood Flooring Adhesive

Tecsun Premium Urethane Wood Flooring Adhesive is warranted for the adhesion to the sub-floor for the installation of all manufacturers of Multi-Ply Engineered Plank, Plain-Back Parquet, Acrylic Impregnated Multi-Ply Engineered Plank and Acrylic Impregnated Plain-Back Parquet on approved sub-floors.

Tecsun Premium Urethane Wood Flooring Adhesive must be used in accordance with Tecsun's most recent installation instructions for Tecsun Urethane Adhesive. Refer to detailed instructions on the adhesive container to determine which wood flooring products can be installed using Tecsun Urethane Adhesive.

The warranty applies only to wood floors installed according to the manufacturer's recommendations for approved sub-floors, pre-installation preparation, including moisture and alkali limitations and job-site conditions.

All conditions and limitations are contained in the specific warranty for Tecsun Urethane Adhesive. Contact Tecsun Building Products' Technical Services for installation recommendations and a copy of the individual product warranty at (626) 968-7566.

07/16/2010