
SPECIFICATION SHEET

ALLURE™ **RANGE HOOD** MODELS QS1, QS2, & QS3



Meeting customer demands for a contemporary styled range hood that is 50% quieter than average hoods, is easy to clean, and brightly lights the cooktop.

FEATURES

- Clean, sleek appearance
- Durable, baked-on polyester finish paint or brushed finish stainless steel
- Over 50% quieter than the average range hood
- Exclusive DuPont Silverstone®, non-stick bottom cover for easy cleaning (QS2 & QS3)
- Large, full filter design dishwasher-safe for easy cleaning
- Dual halogen lights provide focused lighting for unmatched cooktop visibility as well as a soft, night-time level (lamps not
- Patented, axial blade (QS1) or centrifugal blower (QS2 & QS3) uses revolutionary, cyclonic action to increase capture of cooking impurities and odors by 40%
- Flush-mounted controls
- Versatile design allows for 31/4" x 10", 7" round, or non-ducted discharges without re-positioning blower
- Adjustable duct connectors accommodate off-center ductwork
- CleanSense™ charcoal filters change color when replacement is
- necessary (for non-ducted installations purchase separately) Available in 30", 36", or 42" widths in White, Biscuit, Almond, Black, and Stainless Steel
- Bi-lingual carton graphics and installation manual (English/
- Spanish) (English/French Canadian in Canada) Broan Heat SentryTM automatically turns blower to high (QS2), on or higher (QS3) when excess cooking heat is detected

SPECIFICATIONS		MODEL	
	QS1	QS2	QS3
Volts	120	120	120
Hz	60	60	60
Amps	1.7	1.9	2.8
Max. cfm	200	250	250*
Sones (norm.)	1.5	0.9	0.4*
Sones (high)	4.0	3.5	3.5
Controls	2-sp rocker	3-sp electronic	4-sp electronic
Halogen Flood Light	PAR20 [†]	PAR20 [†]	PAR20 [†]
Charcoal Filter	BPSF [‡]	BPSF [‡]	BPSF [‡]
DuPont Silverstone®	No	Yes	Yes
Broan Heat Sentry™	No	Yes	Yes

^{* 400} cfm & 7.0 sones in Boost mode (QS3 only). [‡]Purchase separately for non-ducted installation.

TYPICAL SPECIFICATION


Range hood shall be Broan QS1 (QS2) (QS3) Series.

Unit will have clean, contoured appearance with no sharp edges. Finish to be baked-on polyester paint (matte finish stainless steel). It must have a fully-enclosed bottom and dishwashersafe, full filters.

Hood to be convertible between 31/4" x 10" and 7" round ducted (using two washable aluminum filters) as well as non-ducted (using two CleanSense™ filters - must be purchased separately).
Duct connectors must be adjustable to accommodate off-center ductwork.

Range hood to have a patented, axial blade (centrifugal blower) with cyclonic-action and twin, 50-watt (max.) halogen flood lights. Blower and lights shall be operated using a speciallydesigned, adjustable control with 2-speed rocker (3-speed electronic push button) (4-speed electronic, with delayed "off" and filter reminder).

Air delivery shall be no less than 200 cfm (QS1), 250 cfm (QS2), 400 cfm (QS3). Sound level to be no greater than 1.5 Sones/100 cfm - 4.0 Sones/200 cfm (QS1); 0.9 Sones/100 cfm - 3.5 Sones/ 250 cfm (QS2); 0.4 Sones/100 cfm - 3.5 Sones/250 cfm - 7.0 Sones/400 cfm in "Boost" mode (QS3). Air and sound ratings to be certified by HVI. Unit shall be U.L. and _CU.L. listed.



Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

Broan-NuTone LLC, 926 West State Street, Hartford, WI 53027 (1-800-637-1453) Broan-NuTone Canada, Inc., 1140 Tristar Drive, Mississauga, Ontario, L5T 1H9 (1-888-882-7626)

REFERENCE	QTY.	REMARKS	Project	
			Location	
			Architect	
			Engineer	
			Contractor	
			Submitted by	Date

[†]2 bulbs req. (not included).