





**digital fade dimmers**



- tap on to favorite level; tap off
- tap twice for full on
- press, hold and release for delayed fade-to-off
- touch rocker to adjust light level
- provides true dimming from each location (with companion dimmers)

**incandescent/halogen\***





single pole/multi-location 600W	<b>MA-600-</b>	
single pole/multi-location 600W	<b>MSC-600M-</b>	
single pole/multi-location 1000W	<b>MA-1000-</b>	
single pole/multi-location 1000W	<b>MSC-1000M-</b>	

**incandescent/halogen — eco-dim®\* †** NEW



single pole/ multi-location 600W	<b>MA-600G-</b>	
----------------------------------	-----------------	---

eco-dim® model guarantees at least 15% energy savings compared to a standard switch

**magnetic low-voltage\***

single pole/multi-location 600VA (450W)	<b>MALV-600-</b>	
single pole/multi-location 600VA (450W)	<b>MSCLV-600M-</b>	
single pole/multi-location 1000VA (800W)	<b>MALV-1000-</b>	
single pole/multi-location 1000VA (800W)	<b>MSCLV-1000M-</b>	

**electronic low-voltage\*\***

single pole/multi-location 600W	<b>MAELV-600-</b>	
single pole/multi-location 600W	<b>MSCELV-600M-</b>	

Suggested maximum lighting load for magnetic low-voltage dimming is 450W for 600VA products and 800W for 1000VA products, to allow for transformer losses.

\* minimum load is 40 W/VA

† available in white, ivory, almond, and light almond





\*\* requires neutral wire connection

**fluorescent dimming** with Hi-lume®, Compact SE™, Eco-10®, EcoSystem® ballasts and Hi-lume® LED







- use with Lutron® 3-wire line-voltage control electronic dimming ballasts
- please refer to the Lutron® Fluorescent Dimming Systems Selection Guide (P/N 366-002) for more information
- provides true dimming from each location (with companion dimmers)
- must be derated if ganged



**fluorescent\*\***

single pole/multi-location 6A 120V	<b>MAF-6AM-</b>	<span style="background-color: yellow; border-radius: 50%; padding: 2px;">NEW</span> 
single pole/multi-location 6A 120V	<b>MSCF-6AM-</b>	
single pole/multi-location 6A 277V	<b>MAF-6AM-277-</b>	
single pole/multi-location 6A 277V	<b>MSCF-6AM-277-</b>	

**LED with Hi-lume® LED driver only\*\***

single pole/multi-location 6A 120V	<b>MAF-6AM-</b>	<span style="background-color: yellow; border-radius: 50%; padding: 2px;">NEW</span> 
single pole/multi-location 6A 120V	<b>MSCF-6AM-</b>	
single pole/multi-location 6A 277V	<b>MAF-6AM-277-</b>	
single pole/multi-location 6A 277V	<b>MSCF-6AM-277-</b>	

**LED with GRX-TVI (0-10 VDC sink control)\*\*** NEW

single pole/multi-location 16A load 30 mA control 120/277V	<b>MAF-6AM-</b>	
single pole/multi-location 16A load 30 mA control 120/277V	<b>MSCF-6AM-</b>	



Shown actual size: Maestro® preset digital fade dimmer and 1-gang Satin Colors® wallplate in biscuit (BI)

## MAESTRO® digital fade dimmers

### product family features

- true multi-location dimming from each location
- tap on to favorite level; tap off; tap twice for full on
- touch rocker to adjust light level
- LEDs indicate light level and glow softly in the dark as a locator light
- delayed off provides light as you exit the room
- line frequency compensation maintains stable light
- coordinating Claro® and Satin Colors® wallplates available separately (including stainless steel)
- programming allows customized functions (application note #124 available at [www.lutron.com/applicationnotes](http://www.lutron.com/applicationnotes))
- **eco-dim**® model available

### available models

#### source type

- incandescent/halogen lighting
- magnetic low-voltage lighting
- electronic low-voltage lighting
- fluorescent lighting
- LED lighting
- quiet 7-speed fan controls
- quiet 7-speed fan/light controls
- exhaust fans (countdown timer only)

#### control locations

- single pole (one location)
- multi-location dimming (up to ten locations)

**available colors** (see pages 12-13 for color swatches)

#### colors (gloss finish)

- |                        |                 |
|------------------------|-----------------|
| <b>WH</b> white        | <b>GR</b> gray  |
| <b>IV</b> ivory        | <b>BR</b> brown |
| <b>AL</b> almond       | <b>BL</b> black |
| <b>LA</b> light almond |                 |

#### colors (satin finish)

- |                       |                        |
|-----------------------|------------------------|
| <b>HT</b> hot         | <b>ES</b> eggshell     |
| <b>MR</b> merlot      | <b>BI</b> biscuit      |
| <b>PL</b> plum        | <b>GS</b> goldstone    |
| <b>TQ</b> turquoise   | <b>DS</b> desert stone |
| <b>TC</b> terracotta  | <b>ST</b> stone        |
| <b>GB</b> greenbriar  | <b>LS</b> limestone    |
| <b>BG</b> bluestone   | <b>SW</b> snow         |
| <b>MS</b> mocha stone | <b>PD</b> palladium    |
| <b>SG</b> sea glass   | <b>MN</b> midnight     |
| <b>TP</b> taupe       | <b>SI</b> sienna       |

#### colors & finishes key

- available in gloss finish
- available in satin finish
- available in all gloss and satin finishes

CAD file downloads available at [www.lutron.com/cad](http://www.lutron.com/cad)

Questions on installation or selection?  
Call Lutron® 24 hours/7 days a week at  
1.800.523.9466 or visit [www.lutron.com](http://www.lutron.com)