

digital fade dimmers



- tap on to favorite level; tap off
- tap twice for full on
- press, hold and release for delayed fade-to-off
- touch rocker to adjust light level
- provides true dimming from each location (with companion dimmers)

incandescent/halogen*

single pole/multi-location	600W	MA-600-	
single pole/multi-location	600W	MSC-600M-	
single pole/multi-location	1000W	MA-1000-	
single pole/multi-location	1000W	MSC-1000M-	

incandescent/halogen — eco-dim®* † NEW

single pole/ multi-location	600W	MA-600G-	
-----------------------------	------	-----------------	--

eco-dim® model guarantees at least 15% energy savings compared to a standard switch

magnetic low-voltage*

single pole/multi-location	600 VA (450 W)	MALV-600-	
single pole/multi-location	600 VA (450 W)	MSCLV-600M-	
single pole/multi-location	1000 VA (800 W)	MALV-1000-	
single pole/multi-location	1000 VA (800 W)	MSCLV-1000M-	

electronic low-voltage**

single pole/multi-location	600 W	MAELV-600-	
single pole/multi-location	600 W	MSCELV-600M-	

Suggested maximum lighting load for magnetic low-voltage dimming is 450 W for 600 VA products and 800 W for 1000 VA products, to allow for transformer losses.

* minimum load is 40 W/VA

† available in white, ivory, almond, and light almond

** requires neutral wire connection

fluorescent dimming with Hi-lume®, Compact SE™, Eco-10®, EcoSystem® ballasts and Hi-lume® LED



- use with Lutron® 3-wire line-voltage control electronic dimming ballasts
- please refer to the Lutron® Fluorescent Dimming Systems Selection Guide (P/N 366-002) for more information
- provides true dimming from each location (with companion dimmers)
- must be derated if ganged

fluorescent**

single pole/multi-location	6A 120V	MAF-6AM-	NEW
single pole/multi-location	6A 120V	MSCF-6AM-	
single pole/multi-location	6A 277V	MAF-6AM-277-	
single pole/multi-location	6A 277V	MSCF-6AM-277-	

LED with Hi-lume® LED driver only**

single pole/multi-location	6A 120V	MAF-6AM-	NEW
single pole/multi-location	6A 120V	MSCF-6AM-	
single pole/multi-location	6A 277V	MAF-6AM-277-	
single pole/multi-location	6A 277V	MSCF-6AM-277-	

LED with GRX-TVI (0-10 VDC sink control)**

single pole/multi-location	16A load 30 mA control 120/277V	MAF-6AM-	NEW
single pole/multi-location	16A load 30 mA control 120/277V	MSCF-6AM-	



Shown actual size: Maestro® preset digital fade dimmer and 1-gang Satin Colors® wallplate in biscuit (BI)

MAESTRO® digital fade dimmers

product family features

- true multi-location dimming from each location
- tap on to favorite level; tap off; tap twice for full on
- touch rocker to adjust light level
- LEDs indicate light level and glow softly in the dark as a locator light
- delayed off provides light as you exit the room
- line frequency compensation maintains stable light
- coordinating Claro® and Satin Colors® wallplates available separately (including stainless steel)
- programming allows customized functions (application note #124 available at www.lutron.com/applicationnotes)
- eco-dim® model available

available models

source type

- incandescent/halogen lighting
- magnetic low-voltage lighting
- electronic low-voltage lighting
- fluorescent lighting
- LED lighting
- quiet 7-speed fan controls
- quiet 7-speed fan/light controls
- exhaust fans (countdown timer only)

control locations

- single pole (one location)
- multi-location dimming (up to ten locations)

available colors (see pages 12-13 for color swatches)

colors (gloss finish)

WH white	GR gray
IV ivory	BR brown
AL almond	BL black
LA light almond	

colors (satin finish)

HT hot	ES eggshell
MR merlot	BI biscuit
PL plum	GS goldstone
TQ turquoise	DS desert stone
TC terracotta	ST stone
GB greenbriar	LS limestone
BG bluestone	SW snow
MS mocha stone	PD palladium
SG sea glass	MN midnight
TP taupe	SI sienna

colors & finishes key

- available in gloss finish
- available in satin finish
- available in all gloss and satin finishes

CAD file downloads available at www.lutron.com/cad

Questions on installation or selection?
Call Lutron® 24 hours/7 days a week at
1.800.523.9466 or visit www.lutron.com