Armstrong[®] S-390 Shinekeeper[®] Floor Polish Use and Care

Use For:

- All Armstrong residential semi to high gloss vinyl and linoleum floors
- Asphalt tile
- Rubber tile (not Crowne Disc)
- Ceramic although not much value on glazed ceramic; unglazed other products designed for this use will produce better results
- Slate and terrazzo other products designed for this use will produce better results

Do Not Use For: Wood or marble

FLOOR PREP:

- Sweep or vacuum thoroughly
- Wash with Armstrong Once 'n Done® Floor Cleaner (Do not use Once 'n Done on linoleum)
- Let dry

APPLYING POLISH:

- Pour polish into a clean bucket (never pour polish directly onto floor)
- Apply a thin coat with a clean damp sponge mop or wax applicator
- Make sure the entire surface is coated
- Dries in approximately 30 minutes no buffing necessary

ONGOING POLISHING:

- Reapply Shinekeeper Floor Polish as needed 1 or 2 coats at a time
- If necessary, remove Shinekeeper with Armstrong New Beginning Floor Stripper & Cleaner. Note: Armstrong New Beginning® Floor Stripper & Cleaner cannot be used on linoleum to remove the Shinekeeper. Use a stripper with a pH level no higher than 10 on linoleum.

HOUSEHOLD HINT:

• In high humidity areas, Shinekeeper may take longer than 30 minutes to dry. Keep from freezing. Shelf life is 2 years if unopened.

NOTE: Do not reuse container. Dispose of container and residue in accordance with federal, state and local waste disposal regulations. Do not flush Shinekeeper residue down drains.

Read label carefully before use.