

Armstrong® S-385 Satinkeeper® Low Gloss Floor Finish Use and Care

To preserve the low gloss appearance of all ultra low gloss, low gloss and semi gloss Armstrong residential vinyl sheet, vinyl tile, and linoleum flooring.

Do Not Use For: Hardwood, laminate, cork or marble floors or high gloss vinyl flooring

NOTE: Keep from freezing.

FLOOR PREP:

- Sweep or vacuum thoroughly
- Wash with Armstrong Once 'n Done® Floor Cleaner (Do not use Once 'n Done on linoleum)

APPLYING POLISH:

- Initially, apply two thin coats with a clean damp sponge mop or wax applicator and allow at least 30 minutes drying time between coats
- Make sure the entire surface is coated
- Dries in approximately 30 minutes - **do not buff**

ONGOING POLISHING:

- Reapply Satinkeeper Floor Finish as needed - 1 or 2 coats at a time
- If necessary, remove Satinkeeper with Armstrong New Beginning® Floor Stripper & Cleaner.
Note: Armstrong New Beginning Floor Stripper & Cleaner cannot be used on linoleum to remove the Satinkeeper. Use S-795 Linoleum Stripper instead.

HOUSEHOLD HINT:

- In high humidity areas, Satinkeeper may take longer than 30 minutes to dry

NOTE: Do not reuse container. Dispose of container and residue in accordance with federal, state and local waste disposal regulations. Do not flush Satinkeeper residue down drains.

Read label carefully before use.