



T3, T4

STARLITE BI-PIN LAMPS

Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Lamp Finish	Class & Filament	Avg Rated Life(hrs)	Lumens CCT	LCL (in)	MOL (in)
10	T3	G4 Bipin	58692	142,145	10T3Q/CL/AX	6	40	Clear	C,AXIAL	4000	130 3000	0.88	1.25
			58691	142,145	10T3Q/CL/AX	12	40	Clear	C,AXIAL	4000	130 3000	0.88	1.25
20	T3	G4 Bipin	58694	142,145	20T3Q/CL/AX	12	40	Clear	C,AXIAL	4000	320 3000	0.88	1.25
	T4	GY6.35 Bipin	58663	142,145	20T4Q/CL/AX	12	40	Clear	C,AXIAL	4000	320 3000	1.13	1.75
35	T4	GY6.35 Bipin	58672	142,145	35T4Q/CL/AX	12	40	Clear	C,AXIAL	4000	600 3000	1.13	1.75
50	T4	GY6.35 Bipin	58676	142,145	50T4Q/CL/AX	12	40	Clear	C,AXIAL	4000	910 3000	1.13	1.75
75	T4	GY6.35 Bipin	58680	142,145	75T4Q/CL/AX	12	40	Clear	C,AXIAL	4000	1450 3000	1.13	1.75
90	T4	GY6.35 Bipin	58684	142,145	90T4Q/CL/AX	12	40	Clear	C,AXIAL	4000	1800 3000	1.13	1.75

STANDARD BI-PIN LAMPS

Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Lamp Finish	Class & Filament	Avg Rated Life(hrs)	Lumens CCT	LCL (in)	MOL (in)
5	T3	G4 Bipin	58652	123,140,145	5T3Q/CL	12	40	Clear	C,TR	2000	60 3000	0.88	1.25
			58651	123,141,145	5T3Q/F	12	40	Frosted	C,TR	2000	55 3000	0.88	1.25
10	T3	G4 Bipin	58658	123,140,145	10T3Q/CL	12	40	Clear	C,TR	2000	140 3000	0.88	1.25
			58650	123,140	10T3Q/CL/FP	12	6	Clear	C,TR	2000	140 3000	0.88	1.25
			58656	123,141,145	10T3Q/F	12	40	Frosted	C,TR	2000	130 3000	0.88	1.25
20	T3	G4 Bipin	58661	123,140,145	20T3Q/CL	12	40	Clear	C,TR	2000	320 3000	0.88	1.25
			58655	123,140	20T3Q/CL/FP	12	6	Clear	C,TR	2000	320 3000	0.88	1.25
50	T4	GY6.35 Bipin	58675	123,140	50T4Q/CL	12	40	Clear	C,TR	2000	910 3000	1.13	1.75
			58660	123,140	50T4Q/CL/FP	12	6	Clear	C,TR	2000	910 3000	1.13	1.75

24V BI-PIN LAMPS

Suitable for use in unshielded fixtures.

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Lamp Finish	Class & Filament	Avg Rated Life(hrs)	Lumens CCT	LCL (in)	MOL (in)
20	T3	G4 Bipin	58662	117,143	20T3Q/CL	24	40	Clear	C,AXIAL	1000	320 3000	0.88	1.25
50	T4	GY6.35 Bipin	58678	117,143	50T4Q/CL/AX	24	40	Clear	C,AXIAL	2000	850 3000	1.13	1.75