


# Fuzion 7242 **FUZION 7242 SALON SPA® BATH**

GL50 Fuzion 7242 Salon<sup>™</sup> Spa Right Hand with Chromatherapy lighting GL55 Fuzion 7242 Salon<sup>™</sup> Spa Right Hand with Illumatherapy<sup>™</sup> jet lighting

- GU05 **Optional Wood Frame**
- Center Drain Locations
- Overflow fitting comes with tub
- Accessories / Hardware:

TheraPro Jet Trim Kit: #D095 Oval Trim Kit: #N557 AccuPro Jet trim Kit: # P556 (4 kits required) Optional wood frame in Teak or Wenge finish #GU07

- Trim Kit Finishes Available:
- (827) Chrome
- (898) Brushed Chrome
- (815) Satin Nickel
- (829) Bright Brass
- (805) Platinum




#### Product Shown: GL50 Measurements inside unit represent cutout in

floor to allow for drain/overflow.

Minimum Service Access dimensions given.

#### SIDE VIEW



#### specifications before commencing with any installation work.

**INSTALLATION NOTES** 

PRODUCT SPECIFICATIONS AND AVAILABILITY ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Refer to installation instructions included with fixture before beginning installation. Please confirm product availability and

# **Technical Specifications**

#### DIMENSIONS

72"L x 42" W x 24" H (1829mmL x 1077mmW x 610mmH)

DRAIN LOCATION Center

## CUTOUT

Undermount: GR23000 Drop-In: 71x41

TOTAL WEIGHT 1345 lb / 610 kg

#### **OPERATING GALLONAGE**

108 U.S. Gal Max / 80 U.S. Gal Min 409 Liters / 303 Liters

## PRODUCT WEIGHT

BN60000 (Standard) Dedicated GFCI Circuit

SKIRT MOUNTING Not Available

### **ELECTRICAL SPECIFICATIONS**

### All require a dedicated GFCI protected separate circuit(s).


Motor/Pump: 240 VAC, 20 AMP, 60 Hz Blower: 120VAC, 20 AMP, 60 Hz RapidHeat<sup>™</sup>: 240VAC, 20 AMP, 60 Hz


### HEATER

END VIEW

BN60000 (Standard) Dedicated GFCI Circuit

#### DRAIN / OVERFLOW





#### FAUCET INSTALLATION NOTE:

The combined thickness of the tub shell and optional frame is 1.75". Care should be taken to select a faucet that will accomodate this thickness.

(102

MOTOR