

SPECIFICATION SHEET



Berkshires™ FiberFloor Sheet Flooring

March 23, 2012

PRODUCT SPECIFICATIONS

Series:	L4XXX
Wearlayer:	Vinyl (Low Gloss)
Nominal Wearlayer Thickness:	.005" (0.12mm)
Nominal Total Thickness:	.100" (2.5mm)
Widths:	12' (3.6m)
Maximum Roll Size (Sq. Yds.):	128 (107m ²)
Weight per Sq. Yd. (Lbs.):	3.04 (1.65 kg)
ASTM F-970 Static Load Limit:	75 lbs/in ² (34 kg)

INSTALLATION

Use:	Residential.
Installation System:	Glueless or Full Spread.
Location:	Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.
Seam Method:	Double-cut.

- Room temperature, flooring and adhesive shall be maintained between 65° - 85° F for 48 hours before, during and after installation.
- Use only cementitious based patching and leveling compounds.
- When installing using the Glueless Installation System, leave a 1/4" space between flooring and all verticals (walls, pipes, cabinets, etc.).
- If an installation requires the floor to be net fit, flash coved, installed on steps or if the flooring will be subjected to heavy caster action exceeding the static load limit (i.e. portable dishwashers, microwave carts, wheel chairs, etc.), fully adhere the flooring with recommended adhesive.
- When using the full spread application, roll flooring in both directions with a 75-100 lb. (34-45kg) sectional floor roller.
- Protect sealed seams from all traffic for a minimum of 8 hours.

PATTERN MATCH

• Cantona	L4001	36" x 36", 1/2 drop, Do Not Reverse
• Stella Slate	L4011	36" x 36", Do Not Reverse
• Stone Pavers	L4021	36" x 48", 1/2 drop, Do Not Reverse
• Spanish Marble	L4031	36" x 36", Do Not Reverse
• Richmond Hill	L4041	36" x 36", 2/3 drop, Do Not Reverse

CARE AND MAINTENANCE

- When adhering flooring, do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- Never slide heavy furniture or appliances across the floor. Place plywood on the floor and move the object across the plywood.
- To minimize scratching and indentations, equip tables and chairs with proper floor protectors.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wash floor with a neutral floor cleaner designed for resilient flooring.
- The use of non-staining mats can remove dirt and debris in the entryways and help prolong the life of the floor.
- Maintain post installation temperature between 55° F and 100° F. Maintain relative humidity between 40% and 70%.

WARRANTY

- 20 Year Wear and Manufacturing Defects.



THE ULTIMATE
FLOORING EXPERIENCE