Specifications and Warranties

General:

Description: Dye Method: Dye Resolution: Fiber: Tufted Face Weight: Tuft Bind: Gauge: Pile Height: Primary Backing: Secondary Backing: Secondary Backing (optional): Delamination: Anti-Stain Protection: Antimicrobial Treatment: Broadloom Width: Rug Finishing: Origin:

Performance:

Static Electricity: Traffic: Indoor Air Quality:

Flammability:

Radiant Panel: NBS Smoke Chamber: Methenamine Tablet:

Maintenance:

Spot Cleaning:

Professional Cleaning:

Warranties:

10 Year Texture Retention Limited Warranty
10 Year Abrasive Wear Limited Warranty
10 Year Soil and Stain Protection Limited Warranty
Static Protection
Fade Resistance (for indoor use only)
Limited Manufacturer Defects Warranty

Specifications are subject to normal manufacturing tolerance. Sizes are approximate and actual carpet color may vary.

Cut pile broadloom and rugs Injection dyed 400 dpi STAINMASTER® BCF Type 6,6 2-Ply Premium Nylon 26 oz. / sq. yd. Exceeds industry standards $1/8^{th}$.36 in. Woven polypropylene ActionBac KangaTRAC polyurethane cushion Exceeds industry standards LotusFX Fiber Shield Impervion[®] mold, mildew, and odor treatment 13'6 Bound and serged edges for maximum durability U.S.A.

< 3.5 KV (AATCC-134) Residential or commercial use Green Label Plus Certified



> 0.45 watts/cm² (ASTM – E648, Class I)
 < 450 flaming and non-flaming (ASTM-E662 NFPA-258)
 Self-extinguishing (DOC FF-1-70)

Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly. Hot water extraction.

Fade Resistance (for indoor use only) Limited Manufacturer Defects Warranty

Essentials Cut 26 Fiber: 100% STAINMASTER® Nylon Gauge: 1/8th Face Weight: 26 oz. / sq. yd. Width: 13'6"