

BETTER LIFE TECHNOLOGY, LLC LIMITED PRODUCT WARRANTY WARRANTY COVERAGE

Better Life Technology, LLC (BLT) warrants to the original purchaser (Buyer) only that vinyl mats and flooring product manufactured by Better Life Technology, LLC will be free from defects in material and workmanship under normal use and service for the lifetime of the product. THIS WARRANTY SHALL NOT APPLY AND NO WARRANTY OF ANY KIND SHALL EXIST IF THIS PRODUCT HAS BEEN SUBJECT TO ABUSE, MISUSE, NEGLIGENCE OR ALTERATION OF ANY TYPE OR CAUSE. In addition, BLT is not responsible for defects resulting from improper installation or use, subfloor failures or irregularities, or from uses beyond design capability. In addition to the foregoing limitations, BLT's limited warranty shall not cover surface stains including stains resulting from asphalt, driveway sealer and rubber wheels, defects resulting from improper maintenance or installation, damage from improper usage including, without limitation, burns, cuts, tears, scratches, scuffs, indentation damage from rolling loads, improperly casted carts, damage or discoloration from adhesive or floor care products not recommended by BLT, extended direct exposure to sunlight, excessive moisture, alkaline, hydrostatic pressure damage from the subfloor, mold or mildew, installation over gypsum based patching and leveling compounds or difference in color between samples or photographs and the actual flooring. BLT, in its sole discretion, shall determine whether or not the product is defective or otherwise covered or not covered by this warranty. No action for breach of this warranty may be commenced more than one (1) year after occurrence of the alleged breach. This warranty is not transferable. Customer must notify BLT of all manufacturer defects within 60 days of purchase. Proof of purchase date will be required.

LIMITATION OF LIABILITY

BLT SHALL NOT BE LIABLE FOR THE LOSS OF USE, LOSS OF TIME, INCONVENIENCE, LOSS OF REVENUE OR ANY OTHER INDIRECT, CONSEQUENTIAL, SPECIAL OR INCIDENTAL DAMAGES WHETHER BASED UPON BREACH OF THE ABOVE WARRANTY, BREACH OF CONTRACT, NEGLIGENCE, TORT OR UNDER ANY OTHER LEGAL THEORY. BLT MAKES NO WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED, OTHER THAN AS HEREIN EXPRESSLY PROVIDED AND BLT SPECIFICALLY DISCLAIMS THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

SOME STATES DO NOT ALLOW LIMITS ON WARRANTIES, OR ON REMEDIES FOR BREACH IN CERTAIN TRANSACTIONS, SO THE ABOVE LIMITATION MAY NOT APPLY.

EXCLUSIVE REMEDY

Buyer's remedy for breach of BLT warranty is repair or replacement, at BLT's option, within a reasonable time after notice of defect. In the event that BLT is unable to repair such product, BLT at its option, shall either replace the defective product or refund the purchase price thereof. These remedies are the exclusive remedies for breach of BLT warranty. BLT shall not be liable for any other charges incurred, including installation cost, as a result of a defective product. In the event that Buyer makes any claim under BLT warranty, BLT reserves the right to require any product to be returned for inspection at Buyer's expense, to BLT factory in Emporia, KS. No employee of BLT or any other person is authorized to make any additional warranty or to change this Warranty. Only BLT is authorized to provide warranty service. For warranty information, please call or write to: Customer Service, 9736 Legler Road, Lenexa, KS 66219, Telephone (877) 810-6444.

STOP & READ

Begin by sweeping garage floor clean of debris before unrolling the Garage Floor Protector. Wipe up any oil and chemicals from floor. In most cases, the product is rolled on a PVC or paper core. The product will initially have curl marks—this is normal.

Product Rolled on Core: The warmer the conditions, the quicker the curl marks will straighten out and lay flat. Using a wide push broom, push air out from center and work your way outward side-to-side and length-to-length. Repeat if necessary. Place on garage floor when desired and repeat broom out.

Placement On Garage Floor: For best results, start unrolling process at the garage entrance; finishing at the back of the garage. Using a wide push broom, push any air out from center and work your way outward side-to-side and length-to-length. It will take some time for most curl marks to lay flat. In cool to cold conditions, it may take 72+ hours before all curls have relaxed. Depending on the temperature, product may expand or contract somewhat during process. It is OK to park your car on the Floor Protector during this time.

Trimming & Seaming: For custom fit, allow product to relax in place before trimming around edges and corners. After product has been allowed to relax in place, if you choose to hold down edges or seams between two floor protectors, we recommend using G-Floor Seaming Tape or 3-M® brand 80 Rubber & Vinyl Spray Adhesive to hold edges in place.

Interior, Exterior, or Commercial Use: If product is used under extreme heat, such as direct sunlight, the product may expand or contract a small amount after laying flat. For custom fit, allow product to relax in place before trimming around edges and corners. In exterior and commercial applications, we recommend securing our materials to the floor using a pressure sensitive vinyl adhesive (PSA) or BLT's G-Floor Sheet Adhesive PSA. When installing a vinyl product with adhesive, it must be an acrylic-based product. SBR adhesives (rubber-based) will cause the vinyl flooring to contract. Acrylic-based products are the only adhesives BLT recommends.

The longer it sets, the better it will look

CLEANING & CARE:

Surface is easily washed with floor soap and water. Product can be easily washed off inside or outside of garage. Brush or sweep with cool water using a broom or sponge squeegee. Mild soaps and other household detergents suitable for floors are usually effective. Never leave harsh detergents or chemicals on product. Some people prefer moving the product outside and hosing it off. Normal household vinyl cleaners may be used to increase longevity and to remove stubborn debris. Certain automotive vinyl products may cause surface to become slippery. Use a non-slip vinyl protector such as a clean-and-shine floor cleaner. After cleaning, apply a coat of floor polish for vinyl floors to add a long-lasting, high-luster finish, even to older garage floor protectors. This is not a stain-proof product—certain dyes, inks, rubber tires, and chemicals may cause permanent staining. Some non-permanent stains can be removed with spray-on Brake and Tool Cleaner, found in many auto parts stores. without damaging the product. However, use of Brake and Tool Cleaner may cause product discoloration. Never use harsh chemicals such as tar remover or kerosene on this product.

CAUTION - SAFETY WARNING:

Any floor surface may become slippery when moisture or debris are present. Proper care and cleaning of vinyl flooring will reduce the likelihood of slips and falls. Always wipe up any oil, chemicals, or other fluids that may drip or leak from vehicle to prevent hazardous, slippery conditions. Always dispose of hazardous materials properly. Never leave chemicals on product or wash into sewer system. Leaving chemicals on the product for a long period of time may cause damage. If concrete floor has been treated with certain sealers prior to mat installation, sealer may break down over time and adhere to back of mat without causing damage to mat. Some motorcycle kickstands may cut or damage this product.



For questions please contact:
913.894.0403 • 877.810.6444
customerservice@bltlc.com