


# L4179 Durham

June 1, 2013




## Secure Tuft

Yarn that is regularly found in loop pile carpet is tufted with a straight stitch that may unravel and fray over time. Our Secure Tuft technology allows our carpets to be tufted with an interlocking stitch to prevent unraveling providing the long lasting beauty of your carpet.



## Stain No More

Perfecting the balance between dye technology and understanding a fiber's construction, our carpets feature a Stain No More warranty. Spills can be easily removed through gentle blotting allowing your carpet to remain beautiful in spite of life's little mishaps.



## Scoured & Extracted™ to Stay Clean Longer

This solution dyed carpet is Scoured & Extracted™ to remove the processing oils that attract soil. Scouring makes the carpet easier to clean, and helps prevent accelerated soiling known as Rapid Resoil.



## AccuPattern™

This pattern is guaranteed to run at least 99% straight and true, to ease installation matching. Our computer-controlled AccuPattern™ technology continuously straightens the pattern during the backing process.



## Commercial Warranties

- Lifetime Stain No More
- 10 year Commercial wear
- 10 year Secure Tuft
- 10 year AccuPattern™
- 10 year Anti-Shock

See full text for details.

## Style L4179

01 Sugarcane  
28 Crantini

02 Smoke  
65 Beach House

04 Oakwood  
67 Granite

22 Clay Pot  
71 Mercury

Style L4179 Durham  
 Manufacturer Kraus®

### CONSTRUCTION

|                         |                            |                              |
|-------------------------|----------------------------|------------------------------|
| Fiber system            | 100% BCF Strudon®          |                              |
| Construction            | Patterned multi-level loop |                              |
| Standard backing system | Dual bonding               |                              |
| Pile weight             | 24 oz/y <sup>2</sup>       | 814 g/m <sup>2</sup>         |
| Pile height             | 0.24" / 0.12"              | 6 mm / 3 mm                  |
| Gauge                   | 1/12                       | 47.3 rows/10 cm              |
| Stitches                | 9.0 s.p.i.                 | 35.4 stitches/10 cm          |
| Density                 | 6200                       | 12.1 kilotex/cm <sup>2</sup> |

### PROTECTION

|                       |                      |  |
|-----------------------|----------------------|--|
| Coloration            | Solution dyed        |  |
| Stain resistance      | Stain No More        |  |
| Stain/soil protection | Scoured & Extracted™ |  |

### SUSTAINABILITY

|                          |                  |          |
|--------------------------|------------------|----------|
| CRI/CCI air quality test | Green Label Plus | GLP 4678 |
|--------------------------|------------------|----------|

### PERFORMANCE

|                        |   |  |
|------------------------|---|--|
| Ravel test performance | Construction prevents raveling when tested to PTL-CR (center ravel) and PTL-ER (edge ravel) protocols |  |
| Static generation      | 3.0 kV or less (AATCC 134)  |  |
| Flammability           | CGSB 4GP-129<br>CAN 4-S102.2 (generic per NBC supplement)<br>Radiant Panel ASTM E648 – Class II       |  |
| Colorfastness to light | 5.0 (AATCC 16)  |  |

### INSTALLATION

|                                    |  |               |
|------------------------------------|--|---------------|
| Format                             | 12' wide   | 3.66 m        |
| Approximate pattern repeat (w x l) | 24" x 21"  | 61 cm x 53 cm |
| Recommended adhesive               | Kraus   Premium Adhesive™ KPA-302  |               |
| Installation method                | Suitable for direct glue or cushion installations                                |               |
| Chair protectors                   | Recommended for direct glue installations<br>Mandatory for cushion installations |               |

### WARRANTIES

|            |  |  |
|------------|--|--|
| Warranties | Lifetime Stain No More<br>10 year Commercial wear<br>10 year Secure Tuft<br>10 year AccuPattern™<br>10 year Anti-Shock |  |
|------------|--|--|

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. For best results, seams must be row cut and the carpet must be dry laid to optimize pattern match. Due to dye lot variations, actual material may vary slightly from samples. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice. See [krausflooring.com](http://krausflooring.com) for latest specifications.

E&OE.