


L4199 Elm City

June 1, 2013



Secure Tuft

Yarn that is regularly found in loop pile carpet is tufted with a straight stitch that may unravel and fray over time. Our Secure Tuft technology allows our carpets to be tufted with an interlocking stitch to prevent unraveling providing the long lasting beauty of your carpet.



Stain No More

Perfecting the balance between dye technology and understanding a fiber's construction, our carpets feature a Stain No More warranty. Spills can be easily removed through gentle blotting allowing your carpet to remain beautiful in spite of life's little mishaps.




Scoured & Extracted™ to Stay Clean Longer

This solution dyed carpet is Scoured & Extracted™ to remove the processing oils that attract soil. Scouring makes the carpet easier to clean, and helps prevent accelerated soiling known as Rapid Resoil.



AccuPattern™

This pattern is guaranteed to run at least 99% straight and true, to ease installation matching. Our computer-controlled AccuPattern™ technology continuously straightens the pattern during the backing process.



Commercial Warranties

- Lifetime Stain No More
- 10 year Commercial wear
- 10 year Secure Tuft
- 10 year AccuPattern™
- 10 year Anti-Shock

See full text for details.

Style L4199

01 Sugarcane
28 Crantini
71 Mercury

02 Smoke
31 Pebble

13 Bisque
67 Granite

22 Clay Pot
69 Wheatfield

Style L4199 Elm City
 Manufacturer Kraus®

CONSTRUCTION

Fiber system	100% BCF Strudon®	
Construction	Patterned multi-level loop	
Standard backing system	Dual bonding	
Pile weight	24 oz/y ²	814 g/m ²
Pile height	0.24" / 0.12"	6 mm / 3 mm
Gauge	1/12	47.3 rows/10 cm
Stitches	9.0 s.p.i.	35.4 stitches/10 cm
Density	6200	12.1 kilotex/cm ²

PROTECTION

Coloration	Solution dyed
Stain resistance	Stain No More
Stain/soil protection	Scoured & Extracted™

SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus	GLP 4678
Environmental Awareness	Eligible for any recycling program	

PERFORMANCE

Ravel test performance	Construction prevents raveling when tested to PTL-CR (center ravel) and PTL-ER (edge ravel) protocols	
Static generation	3.0 kV or less (AATCC 134)	
Flammability	CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement) Radiant Panel ASTM E648 – Class II	
Colorfastness to light	5.0 (AATCC 16)	

INSTALLATION

Format	12' wide	3.66 m
Approximate pattern repeat (w x l)	24" x 24"	61 cm x 61 cm
Recommended adhesive	Kraus Premium Adhesive™ KPA-302	
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Recommended for direct glue installations Mandatory for cushion installations	

WARRANTIES

Warranties	Lifetime Stain No More
(See full text for details)	10 year Commercial wear
	10 year Secure Tuft
	10 year AccuPattern™
	10 year Anti-Shock

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. For best results, seams must be row cut and the carpet must be dry laid to optimize pattern match. Due to dye lot variations, actual material may vary slightly from samples. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice. See krausflooring.com for latest specifications.

E&OE.