


# L4922 Mint Hill

June 1, 2013




## Secure Tuft

Yarn that is regularly found in loop pile carpet is tufted with a straight stitch that may unravel and fray over time. Our Secure Tuft technology allows our carpets to be tufted with an interlocking stitch to prevent unraveling providing the long lasting beauty of your carpet.



## Stain No More

Perfecting the balance between dye technology and understanding a fiber's construction, our carpets feature a Stain No More warranty. Spills can be easily removed through gentle blotting allowing your carpet to remain beautiful in spite of life's little mishaps.



## Scoured & Extracted™ to Stay Clean Longer

This solution dyed carpet is Scoured & Extracted™ to remove the processing oils that attract soil. Scouring makes the carpet easier to clean, and helps prevent accelerated soiling known as Rapid Resoil.



## Environmental Awareness

This product is eligible for any recycling program. 100% of this carpet is recyclable.



## Lifetime Warranties

- Commercial wear
- Secure Tuft
- Stain No More
- Anti-Shock
- AccuPattern™

See full text for details.

## Style L4922

08 Spinach Dip  
19 Coastal Shore  
30 Cave Drawing

13 Electric Blue  
21 Nightfall  
34 Sea Rocks

17 English Garden  
23 Spring Bud  
41 Ambrosia

18 Moss Print  
26 Day Break  
46 Stone Road

Style L4922 Mint Hill  
 Manufacturer Kraus®

### CONSTRUCTION

Fiber system	100% BCF Strudon®	
Construction	Interlocking textured loop	
Standard backing system	Dual bonding	
Pile weight	24 oz./y <sup>2</sup>	814 g/m <sup>2</sup>
Pile height	0.16" / 0.08"	4 mm / 2 mm
Gauge	1/10	39.4 rows/10 cm
Stitches	10.0 s.p.i.	39.4 stitches/10 cm
Density	7200	9.7 kilotex/cm <sup>2</sup>

### PROTECTION

Coloration	Solution dyed
Stain resistance	Stain No More
Soil protection	Scoured & Extracted™

### SUSTAINABILITY

CRI/CCI air quality test	Green Label Plus	GLP 4678
Environmental Awareness	Eligible for any recycling program	

### PERFORMANCE

Ravel test performance	Construction prevents raveling when tested to PTL-CR (center ravel) and PTL-ER (edge ravel) protocols	
Static generation	3.0 kV or less (AATCC 134)	
Flammability	CGSB 4GP-129 CAN 4-S102.2 (generic per NBC supplement) DOC FF 1-70	
Colorfastness to light	5.0 (AATCC 16)	

### INSTALLATION

Approximate pattern repeat (w x l)	3/8" x 1/2"	1 cm x 1.5 cm
Installation method	Suitable for direct glue or cushion installations	
Chair protectors	Recommended for direct glue installations Mandatory for cushion installations	

### WARRANTIES

Lifetime Warranties (See full text for details)	Commercial wear Secure Tuft Stain No More Anti-Shock AccuPattern™
--	---

Follow manufacturer's installation recommendations. Correct seam sealing is necessary to prevent seam breakdowns. Due to dye lot variations, actual material may vary slightly from samples. For best results, all seams must be row cut and the carpet must be dry laid to optimize pattern match. The manufacturer reserves the right to modify the specifications to improve the product without notice and without prejudice. \*Percentages of recycled content are accurate at date of printing. The availability of these inputs could fluctuate over time. See [krausflooring.com](http://krausflooring.com) for latest specifications.

E&OE.