


# L4070 Wakefield




## Stain No More

Perfecting the balance between dye technology and understanding a fiber's construction, our carpets feature a Stain No More warranty. Most spills can be easily removed through gentle blotting allowing your carpet to remain beautiful in spite of life's little mishaps.




## Wear

Our carpet is guaranteed to withstand the wear and tear of daily life. Built to perform, our carpet offers strength from face fiber to secondary backing.




## Backing Performance

Carpet tiles are manufactured to provide dimensional stability and will not delaminate from face fiber or edge ravel. Our Backing Performance warranty guarantees that the backing on this product will not shrink, grow, cup or dome, which ensures easy installation and product longevity.



## Modular

Carpet tile has great flexibility in design by mixing colours and patterns you can create your own unique look. Tile is easy to handle and can be installed in stages minimizing renovation downtime. Maintenance or repairs are simple, if a spill occurs the affected tile can be removed and cleaned or simply replaced if damaged, rather than replacing the entire floor.



## 10 Year Warranties

- Commercial Wear
- Backing Performance
- Stain No More

### Style L4070

01 Sandy Shore  
08 At Anchor

02 Even Keel  
09 Battleship

04 Ballast

07 Deep Ocean

Style L4070 Wakefield

**CONSTRUCTION**

---

Fiber system	100% BCF Polypropylene	
Construction	Multi-level scroll loop	
Standard backing system	EuroBac™ Modular	
Pile weight	18 oz./y <sup>2</sup>	610 g/m <sup>2</sup>
Pile height	0.12"	3 mm
Gauge	1/12	47.2 rows/10 cm
Stitches	10.1 s.p.i.	40.0 stitches/10cm
Density	6400	

**SUSTAINABILITY**

---

Environmental Awareness	Eligible for any recycling program
-------------------------	------------------------------------

**PERFORMANCE**

---

Static generation	3.0 kV or less (AATCC 134)
Flammability	Radiant Panel ASTM E648 – Class I (direct glue) DOC FF 1-70 - passes
Colorfastness to light	5.0 (AATCC 16)

**INSTALLATION**

---

Modular size (w x l)	19 5/8" x 19 5/8"	50 cm x 50 cm
Packaging	20 tiles/carton 43 lbs/carton	6 y <sup>2</sup> /carton 32 cartons/pallet
Installation method	Quarter-Turn	

**WARRANTIES**

---

10 Year Warranties (see full text for details)	Commercial Wear Backing Performance Stain No More
---	---

---

The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. While select styles are offered in both modular and broadloom formats, they are not an exact match since the equipment used in the manufacturing of both patterns are entirely different. \*Percentages of recycled content are accurate at date of printing. The availability of these inputs may fluctuate.

---

E&OE.