
FR	IG	IDA		R	E
----	----	-----	--	---	---

Features	
Control Design	Ready-Select™
Digital Display	
Door Latch	Yes
Stay-Put Door Hinge Design	
Low Rinse-Aid Indicator	Yes
Interior Design	Tall Tub
Interior Color	White
Wash System	Direct
Wash Levels	5
Wash Speeds	1
Smart Soil Sensor™	
Sound Package	UltraQuiet™ 3
Filter	Plastic
Filter Trap	Removable
Soft Food Disposer	Yes
dB Level	55
Drying System	Active Vent
Cycles	
Number of Cycles	5
Heavy	Yes
Normal	Yes
Light	Yes
Favorite	
China Crystal	
Rinse Only	Yes
Energy Saver	Yes
Upper Rack Wash Only	
Cycle Indicator Light	
Control Lock	Yes
Options	
Heat/No Heat Dry	Yes
Hi-Temp Wash	Yes
NSF® Certified Sanitize Rinse	Yes
Delay Start	2-4-6 Hour
Rack System	
SpaceWise™ Silverware Basket	Ultra 1
Rack System	Deluxe
Rack Coating	PVC
Rack Handles	1 10
Stemware Holders	
Fold-Down Tines	
Cup Shelf	2
Small Items Cover	
Certifications	
ENERGY STAR®	Yes
NSF® International Certification	Yes
Specifications	103
Water Inlet Location	Loft Bottom Front
Water Usage (Gallons)	Left Bottom Front 6.0
Water Pressure (PSI)	20 - 120
Integral Air Gap on Supply	Yes
Leveling Legs	4
Power Supply Connection Location	Right Bottom Front
Voltage Rating	120V/60Hz/15A
Connected Load (kW Rating) @ 120 Volts <sup>1</sup>	1.44
Amps @ 120 Volts	10
Shipping Weight (Approx.)	64
<sup>1</sup> For use on adequately wired 120V, dedicated cir	

<sup>&</sup>lt;sup>1</sup>For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.





NOTE: Always consult local and national electric and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com.

<b>Product Dimensions</b>	
A-Height (Adjustable)	33-1/2" - 35"
B-Width	24"
C-Depth (Including Door)	25"
D-Depth (To Tub Flange)	22-1/2"
Depth with Door Open 90°	49-1/4"

Cutout Dimensions	
Height (Min.)	34-1/4"
Height (Max.)	35-1/4"
Width (Min.)	24"
Depth (Min.)	24"