

SPECIFICATIONS

SINGLE HANDLE PRESSURE BALANCE TUB & SHOWER FAUCET

Description

- Single handle
- 4" bell style showerhead
- 1/2" slip spout fits 1/2" copper or 1/2" IPS stub-out
- Diverter on spout
- · Back to back installation capabilities

Flow & Valving



Standards

- ASME A112.18.1
- CSA B125
- ASSE 1016
- Energy policy act of 1992
- Listed IAPMO/UPC
- ADA Accessibility Guidelines for Buildings and Facilities - 4.27.4 Controls and Mechanisms 🕭



D510040 (shown) FAIRMONT™

With Diverter & Stops: D510040 (Tub/Shower)

Ġ.

With Stops: D500540 (Shower only)

Available Colors & Finish

- Chrome
- Brushed Nickel (BN)
- Distressed Nickel (DN)
- Oil Rub Bronze (RB)

Trim Kits :

(for use w/pressure balance valves) D510040T (Tub/Shower trim) D500540T (Shower only trim) D500640T (Tub trim w/valve escutcheon)

Special Packaging

- This product also available with valve packaged separate from trim.
- · Use with single handle pressure balance valves: D112000BT (w/stops)
- D115000BT (w/o stops)
- Valves are combination 1/2" copper sweat, 1/2" NPT threaded connectors for all ports.



Danze, Inc., 2500 Internationale Parkway, Woodridge, IL 60517, USA



SPECIFICATIONS

SINGLE HANDLE PRESSURE BALANCE TUB & SHOWER VALVES

Critical Dimensions : Rough-in valve D112000BT (w/stops) & D113000BT (w/diverter & stops) W/SCREWDRIVER STOPS 11/16" (18mm) 3/8"Max ø5/8" 4 1/4" (10mm) (ø16mm) (108mm) 1 9/16" (39mm) PLASTIC GUARD 1 1/16" (27mm) 1/2"-14NPSM (ø152mm) 11/16" ø6" (93mm) Θ Ø 3 1 11/16" (43mm) 26" (660mm) 6 3/4" (172mm) 3 1/16" 2 3/4" (70mm) (77mm) W/DIVERTER & STOPS 11/16" (18mm) ø5/8" (ø16mm) 3/8"Max (10mm) 1 9/16"



Danze, Inc., 2500 Internationale Parkway, Woodridge, IL 60517, USA