


Submitted Model No.:______Specific Features:_____

Min. 2 1/2" (64 mm) Clearance to Back Splash Recommended 9 3/4" 4 1/4" (248 mm) (108 mm) 4 11/16' 3 11/16" (119 mm) (179 mm) (94 mm) 3 X 1 1/8"~1 1/2" (29~38 mm) 1/2"-14 NPSM 1 5/8" 2 7/16" Hole Size (42 mm) Max. Deck ۱۱ (62 mm) 2 1/8" (102 mm) Thickness Centers (53mm) 6 3/8" (162 mm)



▲ Designate Proper Finish Suffix



LAVATORY FAUCET

- Lorain[™] Bath Suite
- Two Handle Deck Mount
- 3 Hole Sink Applications
- 4" Centerset

STANDARD SPECIFICATIONS:

- Two handle lavatory faucets for exposed mounting on 3 hole sinks with 4" centers.
- 4" (102 mm) centerset.
- 4 1/4" (108 mm) long, 7" (179 mm) high spout.
- Hot and cold stems are interchangeable.
- All operating parts are replaceable from the top.
- 1/4 turn handle stops.
- 1/2"-14 NPSM threaded male inlet shanks.
- Control mechanism is a rotating cylinder type with stainless steel plate and 90° rotation, with replaceable non-metallic seats.
- Maximum flow rate 1.5 gpm @ 60 PSI.
- Models have drain with pop-up type fitting with plated flange and stopper.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries





COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2

Indicates compliance to ICC/ANSI A117.1

■ EPA WaterSense®

Verified compliant with 0.25% weighted average Pb content regulations.

