

### Features

- Cast iron with Safeguard® finish
- Left or right drain
- Extra 4" (10.2 cm) ledge
- 60" (152.4 cm) x 34-1/4" (87 cm) x 14" (35.6 cm)


**BATH**  
**K-713**  
**ALSO K-714**

**ADA** **CSA B651** **OBC**

### Codes/Standards Applicable

Specified model meets or exceeds the following:

- ADA
- ICC/ANSI A117.1
- CSA B651
- OBC
- ASME A112.19.1/CSA B45.2



### Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

### Accessories

- 0: White
- CP: Polished Chrome
- PB: Vibrant® Polished Brass
- Other: Refer to Price Book for additional colors/finishes

### Specified Model

Model	Description	Colors/Finishes	
K-713	Bath – left drain	<input type="checkbox"/> 0	<input type="checkbox"/> Other_____
K-714	Bath – right drain	<input type="checkbox"/> 0	<input type="checkbox"/> Other_____

Recommended Accessories				
K-7213	Clearflo bath cable drain with PVC tubing	<input type="checkbox"/> CP	<input type="checkbox"/>	<input type="checkbox"/> Other_____
K-7214	Clearflo bath cable drain without PVC tubing	<input type="checkbox"/> CP	<input type="checkbox"/>	<input type="checkbox"/> Other_____
K-7160-TF	Clearflo pop-up bath drain	<input type="checkbox"/> CP	<input type="checkbox"/> PB	<input type="checkbox"/> Other_____

### Product Specification

The bath shall be made of cast iron with Safeguard finish. Product shall be 60" (152.4 cm) in length, 34-1/4" (87 cm) in width, and 14" (35.6 cm) in height. Product shall have an extra 4" (10.2 cm) ledge. Product shall be available with a left or right drain. Bath shall be Kohler Model K-\_\_\_\_-\_\_\_\_.

**VILLAGER™**

<b>Optional Accessories</b>			
K-1491	Pillow	<input type="checkbox"/> 0	<input type="checkbox"/> Other_____
K-1601	Footstop	<input type="checkbox"/> 0	<input type="checkbox"/> Other_____

## Technical Information

Fixture*:	
Bathing well:	
Basin area, bottom	45" (114.3 cm) x 22" (55.9 cm)
Basin area, top	55" (139.7 cm) x 24" (61 cm)
Weight	330 lbs (149.7 kg)
To overflow:	
Water depth	8-5/8" (21.9 cm)
Capacity	33 gal (124.9 L)
* Approximate measurements for comparison only.	

## Installation Notes


Install this product according to the installation guide.

Floor support under the bath must provide for a minimum of 44 lbs/square foot (215.7 kg/square meter) loading.

Will comply with **ADA** when installed per Section 607  
Bathtubs of the Act.

Will comply with **CSA B651** when installed per Clause 4.4.7 of the standard.

will comply with **OBC** when installed per Clause 3.8.3.13.



### Product Diagram