UL Rated 1-A, 10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Recreational unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- · Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2.5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket



Pt # 466142 - 6 pack UPC: 0-47871-66142-8 I2F - 20047871661422

At a Glance

- Model FA110
- Multipurpose Dry Chemical
- UL listed
- UL rated 1-A,10-B:C
- U.S.C.G, DOT approved
- Supplied with retention strap bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:

Product Specification				
Net agent weight (Average)	2.5 lb.			
Unit weight (Average)	3.9 lb.			
Diameter	3.25 inches			
Height	13.75 inches	1		
Discharge time	8-12 seconds			
Discharge range	6-8 feet	7		
Operating pressure	100 psi			
Cylinder	Seamless aluminum			
Valve, handle, lever	Nylon			
Strap Bracket	U.S.C.G approved			

Packaging Options



Packaging dimensions (inches)

		Depth	Width	Height
	Carton	4.25	3.375	14.31
	Master Pack	21.37	9.5	14.37

