JGSP28DEN

GE® 30"Slide-In Gas Range with Self-Cleaning Oven

D in ensions and Installation Information in inches)

Models are shipped with color-matched Rear Filler Strip KitOptional Kits For Slide-In Electric Ranges Available at additional cost)

ElectricalRequirem ents:120V;60HZ;5A

Lower/Side Trim Kits Accessory Backguards

JXS56 - LowerTrim Kit JXS37 - Backguard

JXS86 - Vertical Side Trim Kit

JXS77 - Body Sides

Note: To reduce possibility of scorching of the side walladjacent to the heating elements, it is recommended a minimum of 6" spacing from adjacent side walls be allowed for possible extended, high-heat, no-bad operation of heating elements.

Receptacle Location: Forall 30" Slide-In Ranges boally approved flexible service cord or conduit must be used because term in als are not accessible after range installation. See shaded area in drawing for boation of electrical outlet box. Recomm ended outlet boations allow range to be installed directly against rearwall.

Note: Cabinets installed adjacent to slide-in ranges must have an adhesion spec of at least 194°.

Installation Inform ation: Before installing, consult installation instructions packed with product for current dimensional data.

For answers to your Monogram, GE Profile or GE appliance questions, visit our website at ge com or call GE Answer Center service, 800 626 2000.



