




Job Name: \_\_\_\_\_

Contact: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Part Number: \_\_\_\_\_

PANDORA

**Description:**

Uni-plug design allows Pandora pendant to be mounted on any lighting system or ceiling canopy through the use of an appropriate adaptor, not included. Standard cable length of 59" can be field-cut or specified when ordering. May be specified with Kiss canopy by adding /MP to part number or /MP2 for 2" version.

**Ordering Code:**

Choose the desired light source, shade color, finish, from the options below.

example: **222 - 856 - bz - MP**

**Light Source:**

**221**  low voltage

**222**  LED

**Shade Colors:**

**855**  sapphire

**856**  garnet

**857**  emerald

**858**  opaline

**Finish:**

**bz**  bronze

**ch**  chrome





**mc**  matte chrome

**Mounting Options:**

**MP** 4" Kiss Canopy

**MP2** 2" Kiss Canopy

# Technical Specs:

| Low voltage                                                                                                                                                                                                                                                              | Low voltage MP                                                                                                                                                                                                                                                                                | Low voltage MP2                                                                                                                                                                                                                                                                                                                                          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                                                                                                         |                                                                                                                                                                                                              |                                                                                                                                                                                                                                                                       |
| <b>221 - xxx</b><br>12V AC/DC input<br>50W, 5VA (max 50 Watt lamp)<br>GY6.35 socket<br>Dimmable<br>Connects to UNI-LIGHT system<br>Suitable for dry locations only                                                                                                       | <b>221 - xxx/MP</b><br>120VAC, 50/60Hz input<br>11.7V AC output 49W, 50VA (max 50 Watt lamp)<br>GY6.35 socket<br>Dimmable (Trailing Edge ELV)<br>Mount to 3 1/2" - 4" round J-Box<br>Suitable for dry locations only<br>Short circuit protection<br>Overload protection<br>Thermal protection | <b>221 - xxx/MP2</b><br>120VAC, 50/60Hz input<br>11.7V AC output<br>49W, 50VA (max 50Watt lamp)<br>GY6.35 socket<br>Dimmable (Trailing Edge ELV)<br>2 1/4" hole cutout<br>Required material thickness 3/16" - 1 1/16"<br>Suitable for dry locations only<br>Not thru-wire rated<br>Short circuit protection<br>Overload protection<br>Thermal protection |
| LED                                                                                                                                                                                                                                                                      | LED MP                                                                                                                                                                                                                                                                                        | LED MP2                                                                                                                                                                                                                                                                                                                                                  |
|                                                                                                                                                                                         |                                                                                                                                                                                                              |                                                                                                                                                                                                                                                                       |
| <b>222 - xxx</b><br>12V AC/DC input<br>700mA CC output 3W, 6VA<br>Connects to UNI-LIGHT system<br>Suitable for dry locations only<br>Compatible with dimmable power supply<br>Compatible with selected Bruck electronic transformers and must meet the minimum VA (load) | <b>222 - xxx/MP</b><br>100-240VAC, 50/60Hz input<br>700mA CC output 3W, 6VA<br>Mount to 3 1/2" - 4" round J-Box<br>Suitable for dry locations only<br>Short circuit protection<br>Thermal protection                                                                                          | <b>222 - xxx/MP2</b><br>100-240VAC, 50/60Hz input<br>700mA CC output<br>3W, 6VA<br>2 1/4" hole cutout<br>Required material thickness 3/16" - 1 1/16"<br>Suitable for dry locations only<br>Not thru-wire rated<br>Short circuit protection<br>Overload protection<br>Thermal protection                                                                  |