

#### Features

- Acrylic
- Rectangular shape
- Molded lumbar supports and armrests
- Drop-in, 4-side integral flange
- 72" (182.9 cm) x 42" (106.7 cm) x 21" (53.3 cm)

# **Codes/Standards Applicable**

Specified model meets or exceeds the following:

• ANSI Z124.1.2



**WINDWARD**<sup>TM</sup>

**BATH** 

# **Colors/Finishes**

- 0: White
- Other: Refer to Price Book for additional colors/finishes

#### Accessories

CP: Polished Chrome

Model	Description	Colors/Finis	Colors/Finishes	
K-1115	Bath – drop-in, rim style	0	Other	
K-1115-F	Bath – drop-in, 4-side integral flange	<b>D</b> 0	Other	
Recommende	ed Accessory			
Recommende K-7166-AF	d Accessory Clearflo pop-up drain OR		□ Other	

# **Specified Model**

### **Product Specification**

The acrylic bath shall be 72" (182.9 cm) in length, 42" (106.7 cm) in width, and 21" (53.3 cm) in height. Bath shall be drop-in or drop-in with 4-side integral flange (-F). Bath shall have molded lumbar supports and armrests. Bath shall be Kohler Model K-1115-\_\_\_\_ or K-1115-F-\_\_\_\_.

# WINDWARD

## **Technical Information**

Fixture*:				
Basin area:				
Bathing well, bottom	55″ (139.7 cm) x 23-1/4″ (59.1 cm)			
Bathing well, top	64" (162.6 cm) x 32" (81.3 cm)			
Weight	100 lbs (45 kg)			
To overflow:				
Water depth	15″ (38.1 cm)			
Capacity	78.5 gal (297 L)			
* Approximate measurements for comparison only.				
Drop-in cut-out dimensions:	70-1/2″ (179.1 cm) x 40-1/2″ (102.9 cm)			

### **Installation Notes**

Install this product according to the installation guide.

Floor support under the bath must provide for a minimum of 38 lbs/square foot (186 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with the drain overflow before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.







WINDWARD™ BATH Page 2 of 2 1047226-4-**C** 

