

# SAN RAPHAELTM

#### **Features**

- Vitreous china
- Elongated bowl
- Comfort Height™
- Includes seat and cover
- Less supply
- One-piece
- Power Lite® operating system (see electrical service requirements)
- 12" (30.5 cm) rough-in
- ADA compliant when installed following installation
- Includes Twin Touch™ actuator to select either 1.0 gal (3.8 L) flush or 1.4 (5.3 L) flush
- 12" (30.5 cm) x 10" (25.4 cm) water area
- 30" (76.2 cm) x 19-1/2" (49.5 cm) x 21-1/2" (54.6 cm)

## **Codes/Standards Applicable**

Specified model meets or exceeds the following:

- ADA
- ASME A112.19.2
- IAPMO/UPC
- Underwriters Laboratories (UL)
- Energy Policy Act of 1992
- ICC/ANSI A117.1
- CSA B45.0
- CSA B45.1
- CSA International
- EPA WaterSense®

# COMFORT HEIGHT™ POWER LITE® TOILET

K-3393





#### Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

#### **Accessories**

- 0: White
- CP: Polished Chrome
- PB: Vibrant<sub>®</sub> Polished Brass
- Other: Refer to Price Book for additional colors/finishes

# **Specified Model**

Model	Description		Colors	Colors/Finishes			
K-3393	Elongated bowl toilet		0	Other			
Optional Accessories							
K-4650	Lustra™ elongated open-front toilet seat - for ADA compliance	□ 0		☐ Other			
K-9433	Twin Touch™ actuator (non-CP)		□ PB	☐ Other			
1098663	Brass riser kit (when local codes require a rigid water supply)						

# SAN RAPHAELTM

### **Product Specification**

The one-piece Comfort Height toilet with elongated bowl shall be made of vitreous china. Toilet shall be 30'' (76.2 cm) in length, 19-1/2'' (49.5 cm) in width, and 21-1/2'' (54.6 cm) in height with a 12'' (30.5 cm) x 10'' (25.4 cm) water area. Toilet shall feature the Power Lite operating system and Twin Touch actuator to select either 1.0 gal (3.8 L) flush or 1.4 gal (5.3 L) flush. Toilet shall be 12'' (30.5 cm) rough-in, and less supply. Toilet shall be ADA compliant (when installed following installation notes). Toilet shall include seat and cover. Toilet shall be Kohler Model K-3393-

#### **Technical Information**

Fixture:	
Configuration	one-piece, elongated
Water per flush	1 gal (3.8 L) or 1.4 gal (5.3 L)
Passageway	2-1/8" (5.4 cm)
Water depth from rim	5-7/8" (14.9 cm)
Water area	12" (30.5 cm) x 10" (25.4 cm)
Seat post hole centers	5-1/2" (14 cm)
Pump	2 Hp, 120 V, 8.5 A, 60 Hz
Minimum static pressure required	15 psi (103.4 kPa)

Included components:		
Tank accessory pack	84301	
Pump	84153	

#### **Required Electrical Service**

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):				
Receptacle	120 V, 15 A, 60 Hz			

#### **Installation Notes**

Install this product according to the installation guide.

Will comply with the American Disabilities Act (ADA) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act, which include the installation of an open front seat.

Section 604 states the required height of the toilet is 17'' (43.2 cm) to 19'' (48.3 cm) from the floor to the top of the seat to meet ADA requirements.







