

Features

- Double quarter-turn ceramic disc valves ensure reliable on/off operation.
- Ceramic disc valves exceed industry longevity standards, ensuring durable performance for life.
- Articulating spout with 360-degree rotation offers superior clearance for filling pots on cooktops and ranges.
- Single lever handle with main lever shutoff. • 22" (559 mm) extended swing spout reach.
- 6.7 gal/min (25.4 l/min) at 60 psi (4.1 bar),
- Coordinates with other HiRise kitchen products.

Material

- Stainless Steel construction.
- KOHLER finishes resist corrosion and tarnishing.

Installation

- Deck-Mount Installation



Codes/Standards

ASME A112.18.1/CSA B125.1

NSF 61

NSF 372

All applicable US Federal and State material regulations

KOHLER® Faucet Lifetime Limited Warranty


See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

| Color | Code | Description |
|-------|------|-------------|
|-------|------|-------------|

| | | |
|--|----|-------------------|
|  | BS | Brushed Stainless |
|--|----|-------------------|



Technical Information

All product dimensions are nominal.

Spout:

Spout reach: 22" (559 mm)

Handle clearance: 2-3/4" (70 mm)

Faucet:

Flow rate: 6.7 gal/min (25.4 l/min)

Pressure: 60 psi (4.1 bar)

Notes

Install this product according to the installation guide.