

# Installation instructions 7 US

CA

Product dimensions	RF135B		E522B	
	inches	mm	inches	mm
<b>A</b> overall height of flat door product	67 <sup>17</sup> / <sub>32</sub>	1715	67 <sup>17</sup> / <sub>32</sub>	1715
<b>A</b> overall height of curved door product	–	–	66 <sup>15</sup> / <sub>16</sub>	1700
<b>A</b> overall height of curved door with ice & water product	–	–	67 <sup>1</sup> / <sub>8</sub>	1705
<b>B</b> overall width of product	25	635	31 <sup>3</sup> / <sub>32</sub>	790
<b>C</b> overall depth of flat door product (excludes handle, includes evaporator)	27 <sup>3</sup> / <sub>8</sub>	695	27 <sup>3</sup> / <sub>8</sub>	695
<b>C</b> overall depth of curved door product (excludes handle, includes evaporator)	–	–	28 <sup>3</sup> / <sub>32</sub>	715
<b>Cabinetry dimensions (including minimum clearances)</b>				
<b>D</b> inside height of cavity	68 <sup>5</sup> / <sub>16</sub>	1735	68 <sup>5</sup> / <sub>16</sub>	1735
<b>Flush with refrigerator chassis – full door rotation</b>				
<b>E</b> inside width	26 <sup>9</sup> / <sub>16</sub>	675	32 <sup>11</sup> / <sub>16</sub>	830
<b>F</b> inside depth	24 <sup>13</sup> / <sub>32</sub>	620	24 <sup>13</sup> / <sub>32</sub>	620
<b>Flush with refrigerator door – full door rotation</b>				
<b>G</b> inside width	31 <sup>3</sup> / <sub>32</sub>	790	37 <sup>7</sup> / <sub>32</sub>	945
<b>H</b> inside depth flush to curved door	–	–	26 <sup>25</sup> / <sub>32</sub>	680
<b>I</b> inside depth flush to flat door	27 <sup>3</sup> / <sub>8</sub>	695	27 <sup>3</sup> / <sub>8</sub>	695
<b>Flush with refrigerator door – 90° door rotation (for full drawer/shelf access, the doors need to be open past 90°)</b>				
<b>J</b> inside width	29 <sup>11</sup> / <sub>32</sub>	745	35 <sup>7</sup> / <sub>16</sub>	900
<b>K</b> inside depth flush to curved door	–	–	26 <sup>25</sup> / <sub>32</sub>	680
<b>L</b> inside depth flush to flat door	27 <sup>3</sup> / <sub>8</sub>	695	27 <sup>3</sup> / <sub>8</sub>	695
<b>Minimum clearances</b>				
<b>M</b> side clearance	2 <sup>5</sup> / <sub>32</sub>	20	2 <sup>5</sup> / <sub>32</sub>	20
<b>N</b> side clearance – hinge side flush with door – full rotation	5 <sup>5</sup> / <sub>16</sub>	135	5 <sup>5</sup> / <sub>16</sub>	135
<b>O</b> side clearance – hinge side flush with door – 90° rotation	3 <sup>17</sup> / <sub>32</sub>	90	3 <sup>17</sup> / <sub>32</sub>	90
<b>P</b> rear clearance (incl. evaporator tray)	1 <sup>3</sup> / <sub>16</sub>	30	1 <sup>3</sup> / <sub>16</sub>	30
<b>Q</b> vent – around top of cupboard (optional)	1 <sup>3</sup> / <sub>32</sub>	50	1 <sup>3</sup> / <sub>32</sub>	50
<b>R</b> top clearance – above refrigerator cabinet	1 <sup>3</sup> / <sub>32</sub>	50	1 <sup>3</sup> / <sub>32</sub>	50
<b>S</b> door clearance – hinge side flush with chassis – full rotation	20 <sup>15</sup> / <sub>32</sub>	520	25 <sup>13</sup> / <sub>32</sub>	645
<b>T</b> door clearance – hinge side flush with door – full rotation	15 <sup>15</sup> / <sub>16</sub>	405	20 <sup>7</sup> / <sub>8</sub>	530