



The Enphase Envoy Communications Gateway is the networking hub for the Enphase Microinverter System.

System owners can easily check the status of their solar system using the Envoy's LCD display or they can get more detailed, per module information through Enlighten, Enphase's web-based monitoring and analysis software, included with purchase of Envoy.

SMART

- Includes web-based monitoring & control
- Integrates with smart energy devices

SIMPLE

- Plug & play installation
- Automatic upgrades & diagnostics

RELIABLE

- 24/7 monitoring & analysis
- Advanced data management & storage



ENVOY COMMUNICATIONS GATEWAY

Interface

Power Line Communications	Enphase proprietary
Local Area Network (LAN)	10/100 auto-sensing, auto-negotiating

Power Requirements

AC supply	120Vac, 60Hz
Power Consumption	2.5 watts typical, 7 watts maximum

Capacity

Number of microinverters polled	Recommended up to 210 For commercial installations, multiple Envoy devices are used in combination with Line Communications Filters (LCF) to separate networking domains across the site.
---------------------------------	--

Mechanical Data

Dimensions (WxHxD)	222.5mm x 112mm x 43.2mm (8.8" x 4.4" x 1.7")
Weight	340g (12oz.)
Ambient temperature range	-40°C to +65°C (-40° to 149°F)
Cooling	Natural convection - no fans
Enclosure environmental rating	Indoor NEMA 1

Features

Standard warranty term	One year
Compliance	UL 60950-1, EN 60950-1 FCC Part 15 Class B

142-00014 Rev 02

Enphase Energy, Inc.

201 1st Street

Petaluma, CA 94952

Phone: +1 707-763-4784

Fax: +1 707-763-0784

info@enphaseenergy.com

<http://www.enphase.com>