

Product Information

Applicable product:	
3/4" top spud urinal	K-5024-T
Fixture:	
Configuration	3/4" top spud
Spud inlet size	3/4"
Water per flush	0.5 gal (1.9 L) or 1.0 gal (3.8 L)*
* Designed to use 0.5 gal (1.9 L) or 1.0 gal (3.8 L) of water when installed with a water saving flushometer.	
Included components:	
3/4" inlet spud	18376
1-1/2" outlet spud	18357
Strainer	85061
1-1/2" tailpiece	38530
Hanger (1 required)	64512
Refer to manufacturer's instructions and local codes for flushometer requirements.	

Recommended accessories:

1-1/2" P-Trap	K-9000
WAVE exposed washout urinal flushometer – 0.5 gpf (1.9 lpf)	K-10675
WAVE exposed washout urinal flushometer – 1.0 gpf (3.8 lpf)r	K-10676
Touchless DC washout urinal flushometer – 0.5 gpf (1.9 lpf)	K-10958
Touchless DC washout urinal flushometer – 1.0 gpf (3.8 lpf)	K-10960
Manual washdown urinal flushometer – 1.0 gpf (3.8 lpf)	K-13518
Manual washdown urinal flushometer – 0.5 gpf (1.9 lpf)	K-13519

Installation Notes

Install this product according to the installation guide.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

*Urinal complies with ADA requirement when rim is mounted no higher than 17" (432 mm) from finished floor

