

## **Product Information**

| Applicable product: |       |
|---------------------|-------|
| Bath – left drain   | K-515 |
| Bath – right drain  | K-516 |

| Fixture*:                                       |                                |  |
|---|--------------------------------|--|
| Basin area:                                     |                                |  |
| Bathing well                                    | 47" (119.4 cm) x 22" (55.9 cm) |  |
| Top area  | 60" (152.4 cm) x 25" (63.5 cm) |  |
| Weight  | 376 lbs (170.6 kg)             |  |
| To overflow:                                    |                                |  |
| Water depth                                     | 10-7/8" (27.6 cm)              |  |
| Capacity  | 47 gal (177.9 L)               |  |
| * Approximate measurements for comparison only. |                                |  |

| Recommended accessories:  |           |
|---|-----------|
| Clearflo adjustable pop-up drain – through-the-floor installation | K-7160-TF |

## **Installation Notes**

Install this product according to the installation guide.

**NOTICE:** By design, the apron is not perpendicular. The bottom edge of the apron angles out approximately 3/4" (1.9 cm) from the top of the rim.

Floor support under bath must provide for a minimum of 54 lbs/square foot (264 kg/square meter) loading.

Will comply with **ADA** when installed per Section 607 Bathtubs of the Act.

Will comply with **CSA B651** when installed per Clause 4.4.7 of the standard.

will comply with **OBC** when installed per Clause 3.8.3.13.

Fixture conforms to ASME Standard A112.19.1/CSA B45.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7160-TF)



