

Product Information

Applicable product:	
6' (1829 mm) bath	K-1249
Fixture*:	
Basin area:	
Bathing well, bottom	50" (1270 mm) x 31" (787 mm)
Bathing well, top	61" (1549 mm) x 34" (864 mm)
Weight	85 lbs (36.8 kg)
To overflow:	
Water depth	14-1/2" (368 mm)
Capacity	86 gal (325.5 L)
* Approximate measurements for comparison only.	
Included components:	
Cut-out template	113927-7
Recommended accessories:	
Pop-up drain OR	K-7161-AF
Cable drain with PVC tubing OR	K-7213
Cable drain without PVC tubing	K-7214

Installation Notes

Install this product according to the installation guide.

Refer to installation instructions included with fixture before beginning installation.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Unless otherwise specified, floor support under bath must provide for a minimum of 40 lbs/square foot (195 kg/square meter) loading.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF)

■ Recommended Faucet Area

