

KOHLER®

Roughing-In

K-1239-H, K-1239-LH, K-1239-RH MARIPOSA® BATH WHIRLPOOL WITH HEATER

Product Information

Applicable product:	
Bath whirlpool with heater – drop-in	K-1239-H
Bath whirlpool with heater – three-wall alcove, left drain	K-1239-LH
Bath whirlpool with heater – three-wall alcove, right drain	K-1239-RH

Fixture*:	
Basin area:	
Bathing area, bottom	46" (1168 mm) x 24" (610 mm)
Bathing area, top	54" (1372 mm) x 27" (686 mm)
Weight	110 lbs (49.9 kg)
To overflow:	
Water depth	14" (356 mm)
Capacity	63 gal (238.5 L)
* Approximate measurements for comparison only.	

Pump		V	Hz	A
1-speed		120	60	7.5
Heater:	Kw	V	Hz	Hz
	1.5	120	60	12.5

Drop-in cutout:

58" (1473 mm) x 34" (864 mm)

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Heater 120 V, 15 A, 60 Hz

Locate the outlets behind the whirlpool and within 24" (610 mm) of the pump and heater.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 44 lbs/square foot (215 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with the drain overflow before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

The apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

