

Product Information

Applicable product:			
Custom bath whirlpool – drop-in			K-1239-CB
Fixture*:			
Bathing well:			
Basin area, bottom	46" (1168 mm) x 24" (610 mm)		
Basin area, top	54" (1372 mm) x 27" (686 mm)		
Weight	105 lbs (47.6 kg)		
To overflow:			
Water depth	14" (356 mm)		
Capacity	63 gal (238.5 L)		
* Approximate measurements for comparison only.			
Drop-in cutout:	58" (1473 mm) x 34" (864 mm)		
Pump:	V	Hz	A
1-speed	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 44 lbs/square foot (214 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with the drain overflow and circulating system before drilling any holes. If installing a spout on the faucet deck, consult local and national codes for minimum air gap requirements.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

