

KOHLER®

Roughing-In

K-1209-LA, K-1209-RA HOURGLASS® 32 BATH WHIRLPOOL WITH INTEGRAL APRON

Product Information

Applicable products:	
Bath whirlpool with integral apron – left drain	K-1209-LA
Bath whirlpool with integral apron – right drain	K-1209-RA

Fixture*:	
Basin area	
Basin area bottom	47" (1194 mm) x 20" (508 mm)
Basin area top	53" (1346 mm) x 23" (584 mm)
Weight	100 lbs (45.4 kg)
To overflow	
Water depth	14-1/2" (368 mm)
Capacity	64 gal (242.3 L)
* Approximate measurements for comparison only.	

Pump:	V	Hz	A
1-speed	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under this product must provide for a minimum of 48 lbs/square foot (234 kg/square meter) loading.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Rim-mount faucet installations: Before drilling the mounting holes, ensure the faucet does not interfere with the drain overflow and circulating system.

Deck-mount spout installations: Consult local and national codes for minimum air gap requirements.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

Recommended Faucet Area

