

KOHLER®

Roughing-In

K-1246-H SEASIDE™ 5' BATH WHIRLPOOL WITH HEATER

Product Information

Applicable product:				
Bath whirlpool with heater – drop-in		K-1246-H		
Fixture*:				
Basin area:				
Bathing well	44” (1118 mm) x 31” (787 mm)			
Top area	50” (1270 mm) x 34” (864 mm)			
Weight	115 lbs (52.2 kg)			
To overflow				
Water depth	15” (381 mm)			
Capacity	69 gal (261 L)			
* Approximate measurements for comparison only.				
Pump:		V	Hz	A
1-speed		120	60	7.5
Heater:	kW	V	Hz	A
	1.5	120	60	12.5
Included components:				
Cut-out template			113926-7	

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Heater 120 V, 15 A, 60 Hz

Locate the outlets behind the whirlpool and within 24" (610 mm) of the pump and heater.


Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 41 lbs/square foot (200 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with the drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.



**Drop-In
Rim Detail**

Pump/Control Access 20" (508 mm)
W x 15" (381 mm) H Min (Typical)

