

KOHLER®

Roughing-In

K-1246-CD, K-1246-CF SEASIDE™ 5' CUSTOM BATH WHIRLPOOL

Product Information

Applicable products:			
Custom bath whirlpool		K-1246-CD	
Custom bath whirlpool		K-1246-CF	
Fixture*:			
Basin area:			
Bathing well	44" (1118 mm) x 31" (787 mm)		
Top area	50" (1270 mm) x 34" (864 mm)		
Weight	110 lbs (49.9 kg)		
To overflow			
Water depth	15" (381 mm)		
Capacity	69 gal (261 L)		
* Approximate measurements for comparison only.			
Pump:	V	Hz	A
1-speed	120	60	7.5
Included components:			
Cut-out template		113926-7	

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 41 lbs/square foot (198 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with the drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Pump must be relocated to custom location at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

