

### Product Information

Applicable product:			
Custom bath whirlpool – drop-in		K-1209-CB	
Fixture*:			
Basin area			
Basin area bottom	47'' (1194 mm) x 20'' (508 mm)		
Basin area top	53'' (1346 mm) x 23'' (584 mm)		
Weight	100 lbs (45.4 kg)		
To overflow			
Water depth	14-1/2'' (368 mm)		
Capacity	64 gal (242.3 L)		
* Approximate measurements for comparison only.			
Pump:	V	Hz	A
1-speed	120	60	7.5

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 50 lbs/square foot (243 kg/square meter) loading.

If installation rim-mount faucet, make sure there is no inference with the drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet desk.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

