

Product Information

Applicable product:				
6' bath whirlpool with heater – drop-in			K-1248-H	
Fixture*:				
Basin area:				
Bathing well		50" (1270 mm) x 31" (787 mm)		
Top area		61" (1549 mm) x 34" (864 mm)		
Weight		117 lbs (53.1 kg)		
To overflow:				
Water depth		14-1/2" (368 mm)		
Capacity		86 gal (325.5 L)		
* Approximate measurements for comparison only.				
Included components:				
Cut-out template			113927-7	
Pump:		V	Hz	A
1-speed		120	60	7.5
Heater:		kW	V	Hz
		1.5	120	60
				12.5

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Heater	120 V, 15 A, 60 Hz
Locate the outlets behind the whirlpool and within 24" (610 mm) of the pump and heater.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 41 lbs/square foot (200 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

Recommended Faucet Area

