

Product Information

Applicable products:			
6' custom bath whirlpool – drop-in			K-1248-CG
6' custom bath whirlpool – drop-in			K-1248-CN
Fixture*:			
Basin area:			
Bathing well	50" (1270 mm) x 31" (787 mm)		
Top area	61" (1549 mm) x 34" (864 mm)		
Weight	112 lbs (50.8 kg)		
To overflow:			
Water depth	14-1/2" (368 mm)		
Capacity	86 gal (325.5 L)		
* Approximate measurements for comparison only.			
Included components:			
Cut-out template			113927-7
Pump:	V	Hz	A
1-speed	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 41 lbs/square foot (198.7 kg/square meter) loading.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

■ Recommended Faucet Area

