

KOHLER®

Roughing-In

K-1126-CN
PROFLEX® 6042
BATH WHIRLPOOL

Product Information

Applicable product:			
Bath whirlpool – drop-in, custom pump			K-1126-CN
Fixture*:			
Basin area:			
Bathing well	46" (1168 mm) x 21" (533 mm)		
Top area	55" (1397 mm) x 31" (787 mm)		
Weight	67-1/2 lbs (30.6 kg)		
To overflow:			
Water depth	14" (356 mm)		
Capacity	57 gal (215.8 L)		
Drop-in cut-out	58-1/4" (1480 mm) x 40-1/2" (1029 mm)		
* Approximate measurements for comparison only.			
Pump:	V	Hz	A
1-speed	120	60	7.5
Recommended accessories:			
Clearflo bath cable drain with PVC tubing			K-7213
Clearflo bath cable drain without PVC tubing			K-7214
Swiftflo™ bath drain			K-11677

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (610 mm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 33 lbs/square foot (159 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677 or K-11677M)

