

# KOHLER®

## Roughing-In

## K-1126-HN PROFLEX® 6042 CUSTOM BATH WHIRLPOOL WITH HEATER

### Product Information

|   |                              |                                       |           |      |
|---|------------------------------|---------------------------------------|-----------|------|
| Applicable product:                             |                              |                                       |           |      |
| Custom bath whirlpool – drop-in                 |                              |                                       | K-1126-HN |      |
| Fixture*:                                       |                              |                                       |           |      |
| Basin area:                                     |                              |                                       |           |      |
| Bathing well                                    | 46" (1168 mm) x 21" (533 mm) |                                       |           |      |
| Top area  | 55" (1397 mm) x 31" (787 mm) |                                       |           |      |
| Weight  | 72.5 lbs (32.9 kg)           |                                       |           |      |
| To overflow:                                    |                              |                                       |           |      |
| Water depth                                     | 14" (356 mm)                 |                                       |           |      |
| Capacity  | 57 gal (215.8 L)             |                                       |           |      |
| * Approximate measurements for comparison only. |                              |                                       |           |      |
|   |                              |                                       |           |      |
| Drop-in cut-out                                 |                              | 58-1/4" (1480 mm) x 40-1/2" (1029 mm) |           |      |
|   |                              |                                       |           |      |
| Pump:   |                              | V                                     | Hz        | A    |
| 1-speed   |                              | 120                                   | 60        | 7.5  |
| Heater:   | kW                           | V                                     | Hz        | A    |
|   | 1.5                          | 120                                   | 60        | 12.5 |

### Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Heater 120 V, 15 A, 60 Hz

Locate the outlets behind the whirlpool and within 24" (610 mm) of the pump and heater.

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 33 lbs/square foot (160 Kg/square meter) loading.

The apron must be installed before the finished floor and wall materials are installed.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677 or K-11677M)

