KOHLER Roughing-In

K-519, K-520 DYNAMETRIC_® BATH

Product Information

Applicable product:		
Bath – left drain		K-519
Bath – right drain		K-520
Fixture*:		
Basin area:		
Bathing well	41" (104.1 cm) x 22" (55.9 cm)	
Top area	54" (137.2 cm) x 25" (63.5 cm)	
Weight	345 lbs (156.5 kg)	
To overflow:		
Water depth	8-5/8" (21.9 cm)	
Capacity	35 gal (132.5 L)	
* Approximate measurements for comparison only.		
Recommended accessories:		
Clearflo adjustable pop-up drain – above K-7160-AF or through-the-floor installation		K-7160-AF

Installation Notes

Install this product according to the installation guide. **NOTICE: By design, the apron is not perpendicular.** The bottom edge of the apron angles out approximately 3/4" (1.9 cm) from the top of the rim.

Floor support under bath must provide for a minimum of 50 lbs/square foot (243 kg/square meter) loading.

Will comply with **ADA** when installed per Section 607 Bathtubs of the Act.

Will comply with $\ensuremath{\text{CSA B651}}$ when installed per Clause 4.4.7 of the standard.

will comply with **OBC** when installed per Clause 3.8.3.13.

Fixture conforms to ASME Standard A112.19.1/CSA B45.2. All dimensions are nominal.



