

### Product Information

Applicable product:	
5.5 bath whirlpool, custom pump	K-1457-HB
5.5 bath whirlpool, custom pump	K-1457-HF
5.5 bath whirlpool, custom pump	K-1457-HJ
5.5 bath whirlpool, custom pump	K-1457-HN

Fixture*:	
Bathing well:	
Basin area, bottom	50" (1270 mm) x 29" (737 mm)
Basin area, top	61" (1549 mm) x 32" (813 mm)
Weight	130 lbs (59 kg)
To overflow:	
Water depth	16" (406 mm)
Capacity	100 gal (378.5 L)
* Approximate measurements for comparison only.	

Pump	kW	V	A*
	1.5	240	11
* Approximate measurements for comparison only.			

Included component:	
Cut-out template	113311-7

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

Recommended faucet area.

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):

Pump/control 208-240 V, 20 A, 50/60 Hz

### Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 48 lbs/square foot (231 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Pump must be relocated to custom position at the time of installation. Provide adequate clearance.

Fixtures conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

