

KOHLER®

Roughing-In

K-1357-H DEVONSHIRE® BATH WHIRLPOOL WITH HEATER

Product Information

Applicable product:				
Bath whirlpool with heater			K-1357-H	
Fixture*:				
Bathing well:				
Basin area, bottom		42" (106.7 cm) x 20" (50.8 cm)		
Basin area, top		51" (129.5 cm) x 24" (61 cm)		
Weight		145 lbs (65.8 kg)		
To overflow:				
Water depth		14" (35.6 cm)		
Capacity		60 gal (227.1 L)		
* Approximate measurements for comparison only.				
Cut-out dimension:				
Drop-in cut-out		58" (147.3 cm) x 30" (76.2 cm)		
Pump:		V	Hz	A
1-speed		120	60	7
Heater:	kW	V	Hz	A
	1.5	120	60	12.5

Required Electrical Service

Two dedicated circuits required, each protected with Class A Ground-Fault Circuit-Interrupter (GFCI):

Pump/control 120 V, 15 A, 60 Hz

Heater 120 V, 15 A, 60 Hz

Locate the outlets behind the whirlpool and within 24" (61 cm) of the pump and heater.

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 50 lbs/square foot (246 kg/square meter) loading.

Fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

K-1357-H

