Product Information

| Applicable product: | | | |
|------------------------------|---------------------------------------|---------|--|
| The Complete Solution toilet | | K-10494 | |
| Fixture: | | | |
| Configuration | two-piece, elongated | | |
| Water per flush | 1.28 gal (4.8 L) | | |
| Passageway | 2-1/8" (54 mm) | | |
| Water area | 11-3/4" (298 mm) x 9-1/2" (241 mm) | | |
| Water depth from rim | 6-1/8" (156 mm) | | |
| Seat post hole centers | 5-1/2" (140 mm) | | |

| Included components: | | |
|--|---------|--|
| Bowl | K-4380 | |
| Tank | K-4434 | |
| Tank cover | 1052862 | |
| Trip lever | K-9167 | |
| Toilet seat | K-4733 | |
| Bolt cap accessory pack | 1013092 | |
| Wax ring and hardware installation kit | 1023457 | |

Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act (ADA) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act, which include the installation of an open front seat.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.8 and 3.8.3.9.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

