



INSTALLATION INSTRUCTIONS

Tools Needed


- Adjustable Wrench • Slip Joint Pliers • Pipe Putty or Teflon Pipe Tape •

1. Shut off hot and cold water supply under sink. Plug sink drain with cloth to avoid losing small parts.
2. Set the faucet in place, insert the inlet shanks through the sink holes, and press down. Assemble the washers and locknuts on the inlet shanks, and then tighten the nuts with hand.
3. Connect the water supply lines. Before connecting the supply lines, apply pipe joint compound to the threads on the inlet shanks and shut off valves with an adjust wrench
4. Turn on water supply valves and check for leaks, especially at hook-ups to supply lines.
5. Turn on your new faucet for the first time. Allow both hot and cold water to run for one minute.




NOTE:

1. Use teflon tape on all threaded connections.
2. Flush line before faucet installation to remove debris
3. Take care not to keep plumber's putty on any finish to corrode finish of faucet surface.
4. Take care not to damage the finish with tools during installation.



Care and Maintenance:

1. To clean, simply wipe with a clean soft cloth.
2. Please do not use sponge. Also, do not use abrasive cleansers or solvents to clean the faucet.




INSTALLATION INSTRUCTIONS

Tools Needed


- Adjustable Wrench • Slip Joint Pliers • Pipe Putty or Teflon Pipe Tape •

PLEASE NOTE: Pop-up assembly/drain assembly is not required for some faucets.


1. Thread mounting nut and bottom gasket onto drain body. Wrap top thread end of drain body with teflon tpe.




2. Slip drain body up through the drain opening and screw seat onto drain body, holding the drain body in position with pivot rod opening facing the back of the sink. Tighten the mounting nut snugly with a wrench.




3. Place pivot rod in pivot rod opening. Slide Pivot nut over pivot rod and thread it on the drain body. Tighten snugly, being careful not to overtighten.



4. With lift rod in position on the faucet, insert lift rod through rod strap and secure with the set screw.



5. Guide the pivot rod through one of the holes on the lift rod strap. Secure it with the spring clip. Adjust the height of the lift rod by resetting the clevis screw.



NOTE: Usage of strong chemicals or cleaners can damage the finish of the drain.