



# ASSEMBLY INSTRUCTION

ITEM# 78200

1. Thread long support screws into holes of the mounting strip. Secure with 5/32" nut.  
The support screws should be long enough to protrude out the canopy when mounted.
  2. Fasten mounting strip onto wall outlet box using two shorter screws .
  3. Connect the wires from the fixture to the power supply wires outlex box.
    - A. Twist together white wire from the fixture with white wire from outlet box. Cover with wire connectors.
    - B. Twist together black wire from the fixture with black wire from outlet box. Cover with wire connectors.
    - C. Wrap the ground wire from the fixture around the green ground screw located on the mounting strip.Tighten the green ground screw to the mounting strip.
  4. Pass back plate through the support screws of mounting strip. Tighten cap nut onto the protruding support screws on mounting strip until the fixture body is held firmly to the wall.
  5. Install the bulb into socket. Do not use greater than 13-watt PL bulb
  6. Screw the nipple into the shelf .
  7. Place the glass onto the socket assembly, then screw the finial into the nipple with cap until tighten.
- NOTE:** Carefully remove the fixture from the carton. Check that all parts shown in package parts 1 and parts 2 are included.  
Be carefully not to misplace any of the screws or wire connectors, which are needed for installing the fixture.

## PACKAGE PART

|                    |   |         |   |
|--------------------|---|---------|---|
| Wire Connectors    | 2 | Cap Nut | 2 |
| Support Screw      | 2 | Bulb    | 1 |
| 5/32" Nut          | 2 | Final   | 1 |
| Green Ground Screw | 1 | Cap     | 1 |
| Outlet Box Screw   | 2 | Nipple  | 1 |
| Mounting strip     | 1 |         |   |

