

Installation Instruction

Warning!!! Shut Power Off At Fuse Or Circuit Breaker

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation.
2. Thread Fixture Wires and Ground Wire thru Center Column, Fasten Center Column to the Connector.
3. Attach Cross Bar to Outlet Box with two Mounting Screws through slot holes at each end of Cross Bar. Note: Cross Bar should be installed with "GND" imprint and two dimples facing down.
4. Fasten one Hex Nut from one end of Threaded Nipple, then screw same end of Threaded Nipple into center hole in Cross Bar. Test and install the Canopy onto ceiling through this Threaded Nipple and make certain 3/8" of Threaded below the Canopy. Once correct Threaded Nipple location has been adjusted, remove Canopy and tighten Hex Nut against Cross Bar. Make certain not to spin Threaded Nipple during tightening. Fasten Screw Collar into one end of Threaded Nipple.
5. Open the Chain link and decide how much Chain to use, Spread open the Chain link you have decided to, remove and discard unused links, and hook the Chain link onto the Fixture Loop then close the Chain link.
6. Slide Collar Ring and then Canopy down the Chain.
7. Open the Chain link at the other end and then hook onto top of Chain,. Then grabbing onto Chain firmly lift fixture and hook the Chain onto Screw Collar which has been mounted onto ceiling, Close back the Chain link.
8. Take the Fixture Ground Wire (Without Plastic Insulation) and weave up through the Chain link, and through Screw Collar and Threaded Nipple. Repeat with Fixture Wires. (With Plastic Insulation)
9. Cut any excess fixture wires and Ground Wire leaving only about 8" length from top end of Threaded Nipple. Then split fixture wires and strip off 3/4" of plastic insulation from each end.
10. Connect the fixture wires to the Outlet Box wires as follows. Connect the White Fixture Wire to the White Supply Wire, Connect the Black Fixture Wire to the Black Supply Wire. Make sure all Wire Connectors are secure and do not easily pull off with the slight tug. If there is no Green Ground Wire from the Outlet Box, connect the Fixture Ground Wire to the Universal Crossbar with the Green Grounding Screw provided.
11. Once all wires are connected, tuck them carefully into Outlet Box. Then raise Canopy against ceiling and lock into position by screwing Collar Ring onto Screw Collar.
12. Secure Threaded Pipe to the bottom of Jointer, slide Plastic Washer, Metal Washer, and Plastic Washer to the Threaded Pipe, put the Crystal Tube and Plastic Washer to the Threaded Pipe, tighten with Finial.
13. Thread Bulb to Socket and slide Outer Glass Shade and Inner Glass Shade to Fitter.
14. Return the power to the Outlet Box and test fixture. Your installation is now complete.

