
ASSEMBLY AND INSTALLATION INSTRUCTIONS FOR ITEM #134F/# 135F

WARNING:

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Should any difficulty be experienced, please consult a qualified electrician

before installing.



- 1. Turn off the electricity at the Fuse or Circuit Breaker before installation.
- 2. Attach the Cross Bar to the Outlet Box by the 2pcs Mounting Short Screws upwards.
- 3. Install Bulbs. (Bulbs are not included, please do not exceed the maximum capacity which is recommended on the Socket Cover.)
- 4. Straight the Central Cluster to be vertical and then fixing the Small Screw.
- 5. Make wire connection with Wire Connectors:
 - ----Connect the black Wire from the light to the Black Wire from the Outlet Box.
 - ----Connect the white Wire from the light to the White Wire from the Outlet Box.
 - ----Attached the Ground Wire and House Ground Wire to the Cross Bar with a Green Screw. Carefully tuck wires back into the Outlet Box.
- 6. There is 1PC extra spare Metal Ball Finial inside the package, you can change the Crystal Ball Finial to be the spare metal piece.
- 7. Raise up the fixture and insert the 2pcs of Long Mounting Screws into the Canopy and tighten with the Fixing Nuts.
- 8. Turn on the power at Fuse or Circuit Box and enjoy your new fixture.