

# Installation Instruction

## WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER

"Note: The installation is for 2, 3, 4 lite, the drawing shown is for representative, not to match your new fixture."

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation. The Model No. shown on the drawings are are representative
2. The Universal Crossbar contains several pairs of threaded holes. Find the pair of holes that match the hole spacing in your fixture Wall Plate, and thread the two Fixture Mounting Screws part way into the Universal Crossbar and tighten with two Hex Nuts.
3. Secure the Universal Crossbar to the Outlet Box by threading the two Outlet Box Screws through the Key Holes.
4. Connect the fixture wires to the Outlet Box wires as follows. Connect the White Fixture wire to the White Supply Wire, Connect the Black Fixture Wire to the Black Supply Wire. Make sure all wire Connectors are secure and do not easily pull off with the slight tug. If there is no Green Ground Wire from the Outlet Box, Connect the Fixture Ground Wire to the Cross Bar with the Green Grounding Screw provided.
5. Once all wires are connected, tuck them carefully into Outlet Box.
6. Place the Wall Plate over the Fixture Mounting Screws, so it protrude through the hole in the Wall Plate
7. Thread the Finial onto the Fixture Mounting Screws and continue turning until the Wall Plate is snug against the wall .
8. Slide Glass Shade and secure Glass Shade by threading Socket Ring onto Socket. Thread Bulb to Socket.
9. Return the power to the Outlet Box and test fixture. Your installation is now complete.

