

A KOHLER COMPANY

Features

- Two toiletry shelves and 18" (45.7 cm) towel bar in backwall for added convenience
- Compression molded from Sterling's exclusive solid VIKRELLTM material
- Modular 4-piece design
- Lightly pebbled bottom surface for sure footing
- Durable swirl gloss finish
- 10 year consumer/3 year commercial limited warranty
- Tongue-and-groove "snap together" design allows for easy installation
- 48" (121.9 cm) x 35-1/4" (89.5 cm) x 73-1/4" (186.1 cm) complete unit rough-in dimensions include flange
- 48" (121.9 cm) x 34" (86.4 cm) x 72" (182.9 cm) complete unit finished dimensions
- 48" (121.9 cm) x 34" (86.4 cm) shower receptors can be ordered separately

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASTM E84
- ANSI Z124.2
- IAPMO/UPC
- HUD, UM Bulletin 73A
- NAHB Research Foundation, Inc.

Specified Model

48" (121.9 cm) SEATED SHOWER **RECEPTOR AND SURROUND** 62030100





Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Complete Unit Description	Colo	rs/Finishes	
48" (121.9 cm) seated shower receptor and wall surround	O White	Other	
Wall Component Description	Color	Colors/Finishes	
Back wall	O White	Other	
Left end wall	O White	Other	
Right end wall	O White	Other	
Complete wall set	O White	Other	
End wall set	O White	Other	
	48" (121.9 cm) seated shower receptor and wall surround Wall Component Description Back wall Left end wall Right end wall Complete wall set	48" (121.9 cm) seated shower receptor and wall surround 0 White Wall Component Description Color Back wall 0 White Left end wall 0 White Right end wall 0 White Complete wall set 0 White	

SterlingPlumbing.com

Visit us online for fixture color choices, detailed product information, color photos, installation instructions, care guides, and warranties. Sterling offers additional lines of plumbing products to complement the Sterling product you've chosen. Sign up for the Sterling monthly e-newsletter which showcases our latest product innovations. You may also call our Sterling Plumbing Answer Center from within the USA at 1-888-STERLING in addition to consulting with your local dealer. Sterling. Strong. Professional. Design.

ADVANTAGE

Technical Information

Model	door maximum width	door maximum height
62030100	44-3/4" (113.7 cm)	67" (170.2 cm)

Installation Notes

Install this product according to the installation guide.

Size the drain cutout to fit the drain assembly that will be used.

End stud positioning is critical if nailing-in flanges are to be used.

Double studding is recommended for pivot shower door installations.

Studs should be positioned roughly as shown for roofing nail installation.



